



MANUAL ANSWITCH V6

Manual anSwitch V6 Operation

Classification: Public
Status: Preliminary
Version: E0.8
Author: D. Bochsler

© Aarenet Inc.

Aarenet, Meriedweg 11
CH-3172 Niederwangen
T +41 31 980 28 11, F +41 31 980 28 12
www.aarenet.com, info@aarenet.com

Contents

| | |
|--|----|
| Manual anSwitch V6 Operation..... | 1 |
| 1 Information About this Manual | 5 |
| 1.1 Purpose of this Documentation | 5 |
| 1.2 Target Audience | 5 |
| 2 The Configuration Interfaces of the anSwitch V6..... | 6 |
| 2.1 Introduction..... | 6 |
| 2.2 ConfigurationCenter..... | 7 |
| 2.2.1 Functionality of the ConfigurationCenter | 7 |
| 2.2.2 Access to the ConfigurationCenter | 7 |
| 2.2.3 Welcome and Main Page | 8 |
| 2.2.4 Navigation and operating elements of the web-based centers..... | 9 |
| 2.2.5 System-wide Configurations for the ConfigurationCenter..... | 9 |
| 2.3 AdminCenter | 10 |
| 2.3.1 Functionality of the AdminCenter..... | 10 |
| 2.3.2 Access to the AdminCenter..... | 10 |
| 2.3.3 Welcome and Main Page | 10 |
| 2.3.4 The AdminCenter Online Help | 11 |
| 2.4 DataAccessCenter | 12 |
| 2.4.1 Functionality of the DataAccessCenter..... | 12 |
| 2.5 Account Management by Export/Import of Excel Files in the ConfigurationCenter..... | 12 |
| 2.5.1 Introduction | 12 |
| 2.5.2 Structure of the Account Excel File..... | 13 |
| 2.5.3 Export the Account Data in XML-Formatted File | 14 |
| 2.5.4 Modify or Add new Accounts in Excel File | 14 |
| 3 User Accounts for Accessing the Configuration Interfaces..... | 15 |
| 3.1 Overview of the User Accounts | 15 |
| 3.2 Manage the User Accounts | 16 |
| 3.3 Configuring the User Account Parameters by an Administrator..... | 16 |
| 3.4 Manage User Account Configuration by the User by the ConfigCenter | 18 |
| 4 Organization Unit "Tenant" & "Group" | 19 |
| 4.1 Overview Organization Unit "Tenant" & "Group" | 19 |
| 4.1.1 Overview of "Tenant" | 19 |
| 4.1.2 Overview of "Group" | 19 |
| 4.1.3 Alternative Usages of a "Tenant" | 20 |
| 4.2 Manage the OrgUnit "Tenant"..... | 21 |
| 4.2.1 Configuring the Tenant Parameters | 21 |
| 4.3 Manage the OrgUnit "Group" | 22 |
| 4.3.1 Configuring the Group Parameters & Attributes | 22 |
| 4.3.2 List of the Group Attributes | 24 |
| 5 The Customer "Account" | 25 |
| 5.1 Introduction to the Central Function of the Account | 25 |
| 5.2 The Provider Defines the Usage of the Account | 25 |

| | | |
|-------|---|----|
| 5.3 | Use-Cases of a Customer Account | 25 |
| 5.3.1 | "Residential" Customer Account | 25 |
| 5.3.2 | "Business" Customer Account | 26 |
| 6 | Manage an Account | 28 |
| 6.1 | Variants of Managing an Account | 28 |
| 6.2 | Managing and Configuring an Account Using the ConfigCenter | 28 |
| 6.3 | Configuring the Account Parameters..... | 29 |
| 6.3.1 | Account Tab "Basic" Parameters | 29 |
| 6.3.2 | Account Tab " Routing & Rating" Parameters..... | 32 |
| 6.3.3 | Account TopStop | 33 |
| 6.3.4 | Account Tab " Advanced" | 36 |
| 6.4 | Display of Concurrent Calls of an Account..... | 38 |
| 7 | Manage Addresses of an Account (Phone Numbers) | 39 |
| 7.1 | Variants of Managing Addresses..... | 39 |
| 7.2 | Managing and Configuring an Address Using the ConfigCenter..... | 39 |
| 7.2.1 | Manage a Single Address | 39 |
| 7.2.2 | Manage an Address Range with the Address Wizard | 39 |
| 7.3 | Configuring the Address Parameters | 42 |
| 7.3.1 | Address Tab "Basic" Parameters..... | 42 |
| 7.3.2 | Address Tab "Advanced" Parameters | 45 |
| 7.3.3 | AdminCenter Account Dialog "Address Administrator" Parameters | 47 |
| 7.3.4 | Address Tab "Answering Machine" (VoiceMail Box) Parameters | 48 |
| 7.3.5 | Address Tab "Virtual PBX" Parameters..... | 48 |
| 8 | Manage the VoiceMail Box of an Address | 49 |
| 8.1 | Overview of the Usage of a VoiceMail Box..... | 49 |
| 8.2 | Configuring the VoiceMail Box Parameters via ConfigCenter..... | 49 |
| 9 | Manage Call Forwards of an Account..... | 52 |
| 9.1 | Overview of a Call Forward CF..... | 52 |
| 9.2 | Managing and Configuring a Call Forward Using the ConfigCenter... | 52 |
| 9.3 | Configuring the Call Forward Parameters | 53 |
| 9.4 | Examples of Call Forwarding..... | 56 |
| 10 | Manage the Attributes of an Account..... | 59 |
| 10.1 | Overview Account Attributes..... | 59 |
| 10.2 | Configure the Account Attribute Parameters..... | 59 |
| 10.3 | List of the Account Attributes..... | 59 |
| 11 | Manage the Emergency Address | 60 |
| 11.1 | Overview of the Emergency Address | 60 |
| 11.2 | Configure the Emergency Address Parameters | 60 |
| 12 | Manage Zone-Profiles for SIP-Device Configuration File Download | 62 |
| 12.1 | Overview Zone-Profiles..... | 62 |
| 12.2 | Configuring Zone-Profile Parameters | 62 |
| 13 | Manage SIP-Profiles of Whitelisted IP-Networks for Phone Registration | 65 |

| | | |
|--------|--|----|
| 13.1 | Overview SIP-Profiles | 65 |
| 13.2 | Configuring SIP Profile Parameters..... | 65 |
| 14 | Manage Web-Profiles of Whitelisted IP-Networks for AdminCenter Access..... | 67 |
| 14.1 | Overview Web-Profiles | 67 |
| 14.2 | Configuring Web-Profile Parameters..... | 67 |
| 15 | Manage SIP-Trunk Profiles for SIP Equipment Communication | 68 |
| 15.1 | Overview of the SIP-Trunk Profile | 68 |
| 15.2 | Use Cases of SIP-Trunk Profiles | 68 |
| 15.3 | Configuring the SIP-Trunk Profile Parameters | 69 |
| 16 | Manage Default Configuration Values of a Customer Account | 77 |
| 16.1 | Overview to the Default Configuration Values | 77 |
| 16.2 | Configuring the Default Configuration Parameters..... | 77 |
| 17 | Deprecated Account and Address Features | 78 |
| 18 | Best Practices | 79 |
| 18.1 | Limit Temporarily an Account | 79 |
| 18.2 | Shutdown an Account..... | 79 |
| 18.2.1 | Different Shutdown Scenarios..... | 79 |
| 18.2.2 | Disabling an Account..... | 80 |
| 18.2.3 | Deleting an Account..... | 81 |
| 19 | Terms of Use | 82 |

1 Information About this Manual

1.1 Purpose of this Documentation

This document describes the configuration, operation and maintenance of the anSwitch V6 customer Accounts.

The following aspects are covered:

- ▶ Description of the configuration of the anSwitch V6 using the web based ConfigurationCenter for administrators and operators, AdminCenter for users.
- ▶ Description User accounts with their roles and scopes of accessing the different resources.
- ▶ Description of how to apply multi-tenancies.
- ▶ Description of the configuration of customer accounts and phone numbers (SIP addresses).
- ▶ Description of configuring profile repositories and how they can be applied to Accounts and Addresses.

1.2 Target Audience

This manual is intended for the following users:

- ▶ Administrators that must set up new Tenants.
- ▶ Administrators that must set up new User accounts.
- ▶ Administrator/Operator that must set up new profiles to be used in Accounts and Addresses.
- ▶ Operators that must set up new customer Accounts and configuring them according to the customer requirements.
- ▶ Supporters who need to help users and customers to solve problems.

2 The Configuration Interfaces of the anSwitch V6

2.1 Introduction

An anSwitch V6 must be configured at various levels to ensure complete and trouble-free operation. Overview of the configuration interfaces:

| Configuration: | Brief description: | Chapter: |
|--|--|-----------------------|
| Operational anSwitch V6 Configuration | All operational configurations are stored in the anSwitch V6 database. All anSwitch V6 components obtain their operational parameters from the database. The database can be fed via various interfaces: | |
| | ConfigurationCenter The ConfigurationCenter is a web-based GUI for administrators, operators and supporters of the anSwitch V6. It allows the configuration of all operational parameters of the anSwitch V6. Different authorization levels (roles) can be used to restrict the options within the ConfigurationCenter. | 2.2 ↗ |
| | AdminCenter Via this web-based GUI, the user or customer can make limited configurations for his number or activate features, e.g. set up call forwarding, listen to voice mail, etc. | 2.3 ↗ |
| | DataAccessCenter The DataAccessCenter is an HTTP/HTTPS based interface that allows 3rd party applications to access the anSwitch V6 data. For example, the operator could use this interface to set up new customer accounts in his CRM system. The interface enables the configuration of all parameters in the anSwitch V6 database. Access is protected by HTTP authentication. The XLS transformation XSLT is supported. | 2.4 ↗ |
| | Other specific interfaces allow a limited configuration of accounts and telephone numbers (SIP addresses): | |
| | Import/Export via ConfigCenter Importing and exporting configuration data using "MS Excel" files enables accounts and addresses to be read, manipulated and written. Deleting is not possible. | 2.5 ↗ |
| anSwitch V6 Components | The anSwitch V6 itself is made up of several interacting components. These anSwitch V6 components are operated as services and - identical to the Linux service - are configured by their configuration files. The anSwitch V6 configuration files are used to make system-wide settings in the anSwitch V6. Aarenet system engineers manage these configuration files and supplement them with system and customer specific settings during commissioning. ➔ The configuration of the anSwitch V6 components is not part of this documentation. | |
| Linux OS & Services | The anSwitch V6 uses the kernel and services of the Linux operating system as integral components of the anSwitch V6, e.g. MySQL database. These services are parameterized by means of their configuration files. Aarenet system engineers manage these configuration files and supplement them with system and customer-specific settings during commissioning. ➔ The configuration of the anSwitch V6 components is not part of this documentation. | |

2.2 ConfigurationCenter

2.2.1 Functionality of the ConfigurationCenter

The ConfigurationCenter is a web-based GUI that can be operated with any modern web browser. It enables the configuration of all operational parameters of the anSwitch V6, e.g. accounts and addresses, activation of user features, call routing, gateway setup, etc. The ConfigurationCenter also provides important sources of information for support.

Access to the ConfigurationCenter is only granted to authenticated users. With authentication, ConfigurationCenter users are each assigned a role that restricts, prevents or even hides the ability to configure or view parameters.

The following roles are available:

- ▶ Administrator
The administrator has all authorizations to configure the anSwitch V6.
- ▶ Operator
Above all, the Operator can set up, change and delete accounts and addresses. He can also perform all the activities of the Supporter.
- ▶ Supporter
The supporter has access to all information that helps to identify and analyze a problem.

The access rights of the roles Administrator, Operator and Supporter can be restricted to the scope of a Tenant.

On demand Aarenet system engineers can create further roles with specific insights and configuration possibilities.

2.2.2 Access to the ConfigurationCenter

Access is possible with any modern web browser. Access is granted with the username and password on the URL specified by the administrator.

For the ConfigurationCenter, the URL must have the following form:

`HTTP://<IP_ADDRESS>:<TCP_PORT>/configcenter`

or

`HTTPS://<DOMAIN>:<TCP_PORT>/configcenter`

The default TCP port is 8443.

Example:

`https://demo.aarenet.com:8443/configcenter`

Note

The options offered in the ConfigurationCenter may differ from the options described below. This is due to the assigned user role and/or enabled features in anSwitch V6.

➔ If in doubt, contact the administrator or operator.


2.2.3 Welcome and Main Page

If contact was established with the ConfigurationCenter via the web browser, the welcome window with the login dialog appears first, e.g.:



The content of the welcome window may vary depending on the system and configuration.

After entering the login credential, the main window of the ConfigurationCenter opens:
















The content of the welcome window may vary depending on the system and configuration.

Note

If the login credentials are entered incorrectly several times, the ConfigurationCenter is blocked for the current HTTP dialog and user for a few minutes

2.2.4 Navigation and operating elements of the web-based centers

The navigation and operating elements are based on current standards:

| Navigation element: | Remark: |
|---|---|
|  | Click on a menu item to open the desired configuration window. |
|  | Update the main window and all open configuration windows. |
|  | All open configuration windows are closed. |
| | In configuration windows with lists, arrows can be used to scroll from one page to the next. A page number can also be entered directly to jump to. |
|  | A search term can be entered in configuration windows with lists. All entries containing the search term are displayed. |
|  | Clicking on the [+] button opens a configuration dialog for a new instance of the object, e.g. a new account, an additional address for an account. |
|  | Click on the [X] button to delete the displayed instance. |
|  | Clicking on the [X] or [Close] button closes a dialog or window without saving and activating any configurations that have been made. |
|  | Click on the [Delete] button to delete the displayed instance. |
|  | By clicking on the [Save] button, the displayed instance is saved and is immediately active. The configuration dialog is not closed. |
|  | Click on the [Ok] button to save the displayed instance and it is immediately active. The configuration dialog is closed. |
|  | Clicking on the [Magnifying glass] button opens a search dialog which allows you to search for the desired entry. |
|  | Click on the [→] button to open the configuration dialog for the associated entity. |
|  | Click on the [Wizard] button to open the wizard dialog, which guides you through the corresponding configuration. |

2.2.5 System-wide Configurations for the ConfigurationCenter

System-wide configurations for the ConfigurationCenter are:

- ▶ The appearance of the welcome and main window.
- ▶ Visibility of menus, dialogs and parameters.
- ▶ Definition of roles.

System-wide settings can be defined for communication with the ConfigurationCenter:

- ▶ The HTTP or HTTPS protocol to be used.
- ▶ The TCP port to be used.

2.3 AdminCenter

2.3.1 Functionality of the AdminCenter

The AdminCenter is the configuration GUI for the user e.g. for selfcare. The "User" can configure personal settings, e.g. call forwarding, accessing the VoiceMail Box, call list etc.

The AdminCenter offers the same configurations as the ConfigCenter but in an optimized view and options for the standard user.

The design of the AdminCenter requires a minimum of design elements so that it can be integrated into an existing provider website.

2.3.2 Access to the AdminCenter

Access is possible with any modern web browser. Access is granted with the username and password on the URL specified by the administrator.

For the AdminCenter, the URL must have the following form:

HTTP://<IP_ADDRESS>:<TCP_PORT>

or

HTTPS://<DOMAIN>:<TCP_PORT>


The default TCP port is 8448.

Example:

<https://demo.aarenet.com:8448>


2.3.3 Welcome and Main Page

If contact was established with the AdminCenter via the web browser, the welcome window with the login dialog appears first, e.g.:



The content of the welcome window may vary depending on the system and configuration.

After entering the login credential, the main window of the ConfigurationCenter opens:



The content of the welcome window may vary depending on the system and configuration.

2.3.4 The AdminCenter Online Help


Check the AdminCenter online help for the handling and configuration possibilities.

For details see the anSwitch V6 [AdminCenter online help](#) .

2.4 DataAccessCenter

2.4.1 Functionality of the DataAccessCenter

The DAML API of the DataAccessCenter allows configuring the anSwitch V6 directly from a customer management system CMS. In a multi-tenant setup of an anSwitch V6 every tenant can have its own CMS application that manages just their own resources.



The anSwitch V6 configuration DAML API cover these general features:

- ▶ Security by:
 - ▶ Individual login and authentication for each CMS application.
 - ▶ Access only to the assigned resources.
- ▶ Secure data transfer by HTTPS.

Note

For detailed information check the anSwitch V6 document: "Manual DataAccessCenter DAML API".

2.5 Account Management by Export/Import of Excel Files in the ConfigurationCenter

2.5.1 Introduction

Account data can be imported or exported to the anSwitch V6 database via the file import/export in the ConfigurationCenter.

This configuration interface is characterized by the following features:

- ▶ Account can be selected and exported in the ConfigurationCenter.
- ▶ Excel files with account data can be imported in the ConfigurationCenter.
- ▶ Accounts can be opened.
- ▶ The basic data of an account can be modified.
- ▶ New addresses can be added to an account.
- ▶ The basic data of an address can be modified.
- ▶ The transfer of data to Excel files enables the configuration of an account without knowledge of the organization in the anSwitch V6 database.

Note

Limitation:
Existing accounts and addresses cannot be deleted!

2.5.2 Structure of the Account Excel File

Warning

The structure of the account Excel file can change with every anSwitch V6 version without notice!

→ These account Excel files must not be used for backup purposes!


The account export file is structured as an XML file and can be edited with an ASCII editor:

```

1  <?xml version="1.0" encoding="UTF-8" standalone="no"?>
2  <?mso-application progid="Excel.Sheet"?>
3  <Workbook xmlns="urn:schemas-microsoft-com:office:spreadsheet" xmlns:html="http://www.w3.org/TR/REC-
4  <DocumentProperties xmlns="urn:schemas-microsoft-com:office:office">
5  <LastAuthor>Martin Schmid</LastAuthor>
6  <LastSaved>2010-01-04T14:44:25Z</LastSaved>
7  <Version>12.00</Version>
8  </DocumentProperties>
9  <ExcelWorkbook xmlns="urn:schemas-microsoft-com:office:excel">
10 <WindowHeight>10005</WindowHeight>
11 <WindowWidth>21600</WindowWidth>
12 <WindowTopX>120</WindowTopX>
13 <WindowTopY>135</WindowTopY>
14 <ProtectStructure>False</ProtectStructure>
15 <ProtectWindows>False</ProtectWindows>
16 </ExcelWorkbook>
17 <Styles>
18 <Style ss:ID="Default" ss:Name="Normal">
19 <Alignment ss:Vertical="Bottom"/>
20 <Borders/>
21 <Font ss:FontName="Arial"/>
22 <Interior/>

```

The exported file is provided with an "MS Excel" <ExcelWorkbook> header. This makes it easy to open the file in "MS Excel" and conveniently edit the data:




| Account | Tenant | Info | Username | Password | Emergency Location | Channels | Routing Table | Pricelist | Voicemail Application | Valid after |
|-------------|-------------|---------------|------------|-----------|--------------------|----------|---------------|-----------------------------|-----------------------|------------------|
| SysMan-0001 | SysMan Comm | Tel 0110 - 19 | 0110 | syf8ss | 3000 Bern | 2 | PSTN | SysMan Communication - Sale | | 01.03.2010 12:00 |
| SysMan-0002 | SysMan Comm | Tel 0220 - 29 | 0220 | w45fzwtb6 | | | PSTN | SysMan Communication - Sale | | 01.03.2010 12:00 |
| SysMan-0003 | SysMan Comm | Tel 0330 - 39 | sysman017K | wc456v3 | | | PSTN | SysMan Communication - Sale | | |
| SysMan-0004 | SysMan Comm | | sysmanglmD | wegrtw45z | | | | | | |


The various configuration topics are organized in spreadsheets and can be edited directly. The configurations are assigned using the account name in the first column of each worksheet. Multiple entries, e.g. addresses of an account, always start with the identifying account name:

Account-Parameter : SysMan-0001


Account-Parameter: SysMan-0002



| Account | Tenant | Info | Username |
|-------------|-------------|---------------|------------|
| SysMan-0001 | SysMan Comm | Tel 0110 - 19 | 0110 |
| SysMan-0002 | SysMan Comm | Tel 0220 - 29 | 0220 |
| SysMan-0003 | SysMan Comm | Tel 0330 - 39 | sysman017K |
| SysMan-0004 | SysMan Comm | | sysmanglmD |




| Account | Number | Roman | Displayname |
|-------------|--------|-----------|-------------|
| SysMan-0001 | 4445 | 81.6.1.53 | hallo 45 |
| SysMan-0001 | 4446 | 81.6.1.53 | hallo 46 |
| SysMan-0001 | 4444 | 81.6.1.53 | hallo 44 |
| SysMan-0001 | 0110 | 81.6.1.53 | |
| SysMan-0001 | 0114 | 81.6.1.53 | |
| SysMan-0001 | 0117 | 81.6.1.53 | |
| SysMan-0001 | 0111 | 81.6.1.53 | |
| SysMan-0001 | 5555 | 81.6.1.53 | |
| SysMan-0001 | 5556 | 81.6.1.53 | |
| SysMan-0001 | 0115 | 81.6.1.53 | |
| SysMan-0001 | 0116 | 81.6.1.53 | |
| SysMan-0001 | 0118 | 81.6.1.53 | |
| SysMan-0001 | 0119 | 81.6.1.53 | |
| SysMan-0001 | 0112 | 81.6.1.53 | |
| SysMan-0001 | 4447 | 81.6.1.53 | hallo 47 |
| SysMan-0001 | 6666 | 81.6.1.53 | |
| SysMan-0001 | 6667 | 81.6.1.53 | |
| SysMan-0001 | 7777 | 81.6.1.53 | bla |
| SysMan-0001 | 7778 | 81.6.1.53 | bla |
| SysMan-0001 | 6888 | 81.6.1.53 | |
| SysMan-0001 | 6889 | 81.6.1.53 | |
| SysMan-0002 | 0221 | 81.6.1.53 | |
| SysMan-0002 | 0220 | 81.6.1.53 | |
| SysMan-0002 | 0222 | 81.6.1.53 | |
| SysMan-0002 | 0223 | 81.6.1.53 | |
| SysMan-0002 | 0224 | 81.6.1.53 | |
| SysMan-0002 | 0225 | 81.6.1.53 | |
| SysMan-0002 | 0226 | 81.6.1.53 | |
| SysMan-0002 | 0227 | 81.6.1.53 | |



| Account | RuleSet Name |
|-------------|-----------------|
| SysMan-0001 | Block 090 Calls |
| SysMan-0001 | Subscriber |
| SysMan-0002 | Subscriber |
| SysMan-0002 | Block 090 Calls |
| SysMan-0003 | Subscriber |

Most entries are character strings, such as for the Account parameter. If the possible parameter values are specified by the system, they can be selected using a selection list:



2.5.3 Export the Account Data in XML-Formatted File

Log in the ConfigCenter as Administrator/Operator

-
- > Menu: Accounts
 - > Search for the desired account or accounts
 - ➔ The displayed accounts will be exported!
 - > Click button: Export
-
- > Rename and save the generated file "accounts.xml" if necessary.
-

2.5.4 Modify or Add new Accounts in Excel File


It is assumed that exported "accounts.xml" was modified with e.g. MS Excel:

Modify existing values.

Add new accounts with their properties and values.

➔ Before importing make sure that the modified account file is XML formatted.

-
- > Menu: Accounts
 - > Click button: Import
-
- > Select the to import file in dialog: File Upload
 - > Click button: Upload file
-
- > A consistency check is first carried out before the data can be saved.
 - > In case of an error the dialog "File Import" click button: Details
-



Check the displayed details for evaluating the problem.


-
- > Click button: Save, when the data are consistent.
-

3 User Accounts for Accessing the Configuration Interfaces

3.1 Overview of the User Accounts

Every user that must access the ConfigCenter needs a user account. The account is also valid for accessing the AdminCenter.

The anSwitch V6 landscape of the different user accesses:



Overview of the different roles and their responsibilities:

| AdminCenter | ConfigCenter | DAML API | System Engineer |
|---|---|--|--|
| Roles: <ul style="list-style-type: none"> vPBX Administrator vPBX Installer User System Administrator Tenant Administrator Tenant Operator Tenant Supporter | Roles: <ul style="list-style-type: none"> System Administrator Tenant Administrator Tenant Operator Tenant Supporter | Roles: <ul style="list-style-type: none"> Access profile | Roles: <ul style="list-style-type: none"> Access profile |
| Access: <ul style="list-style-type: none"> Web GUI (PC & Mobile) | Access: <ul style="list-style-type: none"> Web GUI | Access: <ul style="list-style-type: none"> HTTPS/XML | Access: <ul style="list-style-type: none"> SSH/SSL, Command line |
| Description of the Roles: <ul style="list-style-type: none"> The "vPBX Administrator" can configure and manage the vPBX and its extensions. The "vPBX Installer" can configure and manage all vPBXs of its vPBX group. The "User" can configure and manage its own vPBX extension or residential access. The "System Administrator" can manage all vPBX. The "Tenant Administrator, Operator, Supporter" can manage all vPBX of its tenant. | Description of the Roles: <ul style="list-style-type: none"> The "System Administrator" can configure the whole VoIP switch. He has all rights. The "Tenant Administrator" can configure all resources of its tenant. This role has also the operator and supporter rights. The "Tenant Operator" configures and manages the accounts of its tenant. This role has also the supporter rights. The "Tenant Supporter" can access the support tools and modify the accounts of its tenant. | Description of the Roles: <ul style="list-style-type: none"> The providers CRM system can configure and manage accounts via the DAML API. Each tenant may have its own access profile which defines the manageable objects and ensures that only accounts of its tenant are accessible. | Description of the Roles: <ul style="list-style-type: none"> The "System Engineer" has access to configure and manage the Aarenet VoIP Switch components. He can perform system wide configurations and maintenance on all VoIP System devices. |

A user with the role of Administrator can create and manage user accounts for the ConfigurationCenter. A user account consists of these data:



- ▶ Name and password of the user account.
- ▶ Which role is granted to the user.
- ▶ Resources the user is allowed to access.
- ▶ Which language is used in the ConfigurationCenter for this user.
- ▶ Two-Factor and/or LDAP authentication is applied.
- ▶ Email address for password recovery (via AdminCenter login only).
- ▶ Deblocking a user account.

The roles are generally assigned the following authorizations:


- ▶ Administrator:
The user can manage all resources of the anSwitch. The access can be limited to scope of a tenant.
- ▶ Operator:
The user can manage all accounts and its related resources of the anSwitch V6. The Operator has access to all anSwitch V6 support tools. The access can be limited to the scope of a tenant.
- ▶ Supporter:
The user can read all accounts and its related resources of the anSwitch V6. The Supporter has access to some anSwitch V6 support tools. The access can be limited to the scope of a tenant.

3.2 Manage the User Accounts

For the creation, modifying or deleting a User account, login as Administrator:

- > Menu: System
 - > Sub-Menu: Users
 - > The dialog "Users" is displayed. It allows:
 - ▶ To create a user account, click icon 
 - ▶ Modify and delete a user account, click the row of the desired account.
 - ▶ Delete a User account click icon  or click the button "Delete" in the dialog "User: ..."
 - > Configure the user account in dialog: User
 - > Parameter list, see below
 - > Click button: Save

3.3 Configuring the User Account Parameters by an Administrator



| Parameter Name | Data Type | Allowed Values | Description |
|---------------------|-----------|--|---|
| Username | String | [empty Max. 128 char] Default: empty | Defines the username for this user. |
| New Password | String | [empty Max. 128 char] Default: empty | Defines the password for this user. |
| Verify New Password | String | | Re-enter the password for check. |
| Renew Password | Selection | [No Yes] | Defines if the password must be changed by the user upon the first login. |

| Parameter Name | Data Type | Allowed Values | Description |
|------------------------------|--------------------------|--|---|
| | | Default: No | |
| Role | Selection | [Supporter Operator Administrator PBX Installer PBX Administrator] Default: Supporter | Defines the role of the user. Values: <ul style="list-style-type: none"> ▶ Administrator: The user can read all accounts and its related resources of the anSwitch V6. The Supporter has access to some anSwitch V6 support tools. ▶ Operator: The user can manage all accounts and its related resources of the anSwitch V6. The Operator has access to all anSwitch V6 support tools. ▶ Supporter: The user can read all accounts and its related resources of the anSwitch V6. The Supporter has access to some anSwitch V6 support tools. ▶ PBX Installer: ▶ PBX Administrator: Deprecated. Defines the access to a certain vPBX or list of vPBXs. |
| Tenant | Selection | [- (none) List of configured tenants] Default: - (none) | Defines the scope of the accessible resources for the user. Values: <ul style="list-style-type: none"> ▶ - (none): No limitations ▶ Name: Defines the tenant resources the user has access to. |
| Language | Selection | [English German Vietnamese] Default: English | Defines the language of the ConfigCenter configuration pages. |
| E-Mail Address | Email Address | [empty Max. 128 char] Default: empty | Defines the email address where password recovery information for the AdminCenter is sent to. |
| Login is blocked | Selection | [No Yes] Default: No | Displays if the account is blocked by too many unsuccessful login attempts. Unblock the account by selecting "Yes" |
| Two Factor Authentication | <input type="checkbox"/> | Activate Default: Not activated | If activated, defines that the login to the AdminCenter is secured by a two-factor authentication. |
| LDAP Authentication | | | Defines the user authentication against a LDAP service. ➔ Check with the Aarenet support for configuration. |
| LDAP Authentication Template | | | |
| LDAP Authentication URL | | | |
| LDAP Authentication secure | | | |

3.4 Manage User Account Configuration by the User by the ConfigCenter

The user can manage its own user account:

- > Menu: Settings
- > The dialog "Settings" is displayed. It allows:
 - > To modify the own user account
 - > Configure the user account in dialog: Settings
 - > Parameter list, see below
 - > Click button: Save

Note

If the password is lost, contact an Administrator. The Administrator can define a new temporary password for each role.

| Parameter Name | Data Type | Allowed Values | Description |
|---------------------|---------------|---|---|
| Username | String | [empty Max. 128 char] Default: empty | Defines the username for this user. |
| New Password | String | [empty Max. 128 char] Default: empty | Defines the password for this user. |
| Verify New Password | String | | Re-enter the password for check. |
| Language | Selection | [English German Vietnamese] Default: English | Defines the language of the ConfigCenter configuration pages. |
| E-Mail Address | Email Address | [empty Max. 128 char] Default: empty | Defines the email address where password recovery information for the AdminCenter is sent to. |


4 Organization Unit "Tenant" & "Group"

4.1 Overview Organization Unit "Tenant" & "Group"

4.1.1 Overview of "Tenant"

A "Tenant" defines an organization unit that is used for separating multiple "Telephone Service Providers" that share the same anSwitch V6.

A "Tenant" is used to bundle accounts and resources that are just available and visible to the tenant's Administrators, Operators and Supporters.



A "Tenant" can manage the following resources of its own:

- ▶ Customer Accounts
- ▶ Concerning the call routing:
 - ▶ RuleSets
 - ▶ Numbering Plans
 - ▶ Routing Tables
 - ▶ Gateways
- ▶ Concerning the Rating:
 - ▶ Pricelists for its customers
 - ▶ Pricelists for purchasing at PSTN carriers.
 - ▶ Rating reports
- ▶ Concerning the configuration:
 - ▶ Tenant Administrator access
 - ▶ Tenant Operator access
 - ▶ Tenant Supporter access
 - ▶ DAML API access
 - ▶ Default configurations for new account.


For assigning specific behaviors and limits to a "Tenant" a specific "Group" has to be associated.

4.1.2 Overview of "Group"

The "Group" defines a hierarchical structured organization unit that allows to assign values and behaviors to its members, e.g. tenant:

- ▶ The "Group" manages configurations like e.g., max. number of concurrent channels per tenant.
- ▶ The "Group" configurations are managed with attributes which assign the desired property and its value to e.g. a tenant.
- ▶ A "Group" can have child-groups:
 - ▶ Inherit the attributes and behaviors from its parent.


- ▶ Can overwrite values that are inherited from its parent group.
- ▶ (Deprecated: The "Group" behaviors are determined by their "Type", e.g. vPBX.)



4.1.3 Alternative Usages of a "Tenant"



The concept of "Tenant" can also be used e.g. administrative separation of resources, different types of offerings or access control for Operators/Supporters:

- ▶ If certain resources in an anSwitch V6 , e.g. gateways, should not be visible to all, it is advisable to open a tenant with the name "System" and assign all these resources to the "System". These resources are then only accessible to e.g. system administrators.
- ▶ Organize e.g. residential accounts in a tenant and business customers with SIP-trunk in a different tenant.
- ▶ Create a sandbox tenant where to test new configurations of resources, e.g. RuleSet, Routing Tables, etc.




4.2 Manage the OrgUnit "Tenant"








Adding a new Tenant or managing an existing one, open the ConfigCenter as system Administrator or Operator.

- > Menu: System
 - > Sub-Menu: Tenants
 - > The dialog "Tenants" is displayed. It allows:
 - ▶ To create a new Tenant, click icon 
 - ▶ Modify and delete a Tenant, click the row of the desired Tenant.
 - ▶ Delete a Tenant click icon  or click the button "Delete" in the dialog "Tenant: ..."

4.2.1 Configuring the Tenant Parameters





| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|---|---|
| Name | String | [empty Name, max. 64 char] Default: empty | Defines the name of the tenant. |
| Pricelist | Selection | [- (none) List of configured and allowed pricelists] Default: - (none) | Defines an optional price list that is used for computing the charges of a connection the tenant has to pay to e.g. PSTN Carrier. Values: <ul style="list-style-type: none"> ▶ - (none): No pricelist assigned, then no connection charges can be computed. ▶ Selected price list: Defines the price list to use. |
| Channels | Number | [empty ≥ 0] Default: empty | Defines the limitation of concurrent connection for the tenant. Values: <ul style="list-style-type: none"> ▶ empty: No limitations ▶ 0: No connections are possible. ▶ ≥ 1: Limit of max. concurrent connections. |
| CDR lock | Selection | [not locked List of the last three month] Default: not locked | Defines how long the CDRs of the tenant must not be changed or deleted in the CDR database. This setting can override the value of the system CDR cleanup task. Values: |


| Parameter Name | Data Type | Allowed Values | Description |
|----------------|----------------|---|---|
| | | | <ul style="list-style-type: none"> ▶ not locked: The CDRs are not locked. ▶ List selection: The CDR lock period. |
| Group | Display & link | Group   | Displays if the tenant has an associated group with the same name.  is the link to the group configuration, details see "Manage the OrgUnit "Group""  . |
| Addresses | Display & link | Addresses 12 Addresses  | Displays the number of active SIP addresses of this tenant.  is the link to the address list of this tenant, details see "Manage Addresses of an Account (Phone Numbers)"  . |

4.3 Manage the OrgUnit "Group"

Adding a new Group or managing an existing one, open the ConfigCenter as system Administrator or Operator.

- > Menu: System
 - > Sub-Menu: Groups
 - > The dialog "Groups" is displayed. It allows:
 - ▶ To create a new Group, click icon 
 - ▶ Modify and delete a Group, click the row of the desired Group.
 - ▶ Delete a Group click icon  or click the button "Delete" in the dialog "Group: ..."

4.3.1 Configuring the Group Parameters & Attributes



The screenshot displays three overlapping dialog boxes in the Aarenet ConfigCenter. The 'Group: Provider A' dialog is in the background, showing fields for Tenant (Provider A), Parent Group, Attributes (2 Attributes), Name (Provider A), Info, and Type. The 'Attributes for Group: Provider A' dialog is in the middle, showing a table with 2 entries: 'anCsDomain' with value 'CLID_TRAIN_E' and 'ZONE' with value 'Default'. The 'New Group Attribute' dialog is in the foreground, showing fields for Name (ZONE) and Value.

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|---|--|
| Tenant | Selection | [- (none) List of configured and allowed tenants] Default: - (none) | Defines the tenant this group belongs to. Values: <ul style="list-style-type: none"> ▶ - (none): No parent assigned. ▶ Tenant: Defines the selected tenant this group belongs |
| Parent Group | Selection | [- (none) List of configured and allowed groups] Default: - (none) | Defines the parent group of this group. This group inherits all configurations from its parent group unless the parameters or |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|----------------|--|--|
| | | | attributes overwrite the corresponding values from the parent. Values: <ul style="list-style-type: none"> ▸ - (none): No parent group assigned. ▸ Group: Defines the selected parent group. |
| Attributes | Display & Link | 2 Attributes ➡ | Displays if the number of attributes defined in this group. ➡ is the link to the attribute configuration. It opens the dialog with the list of assigned attributes and allows to manage the attributes. |
| Name | String | [empty Name, max. 64 char] Default: empty | Defines the name of the group. Note: If the group is associated with a tenant , then its name must be identical to the tenant! |
| Info | String | [empty Name, max. 128 char] Default: empty | Any information about this group |
| Type | Selection | [- (none) PBX Department] Default: - (none) | Defines the group type. Values: <ul style="list-style-type: none"> ▸ - (none): → Use this for groups associated with a tenant. ▸ PBX, Department: → Deprecated Defines a vPBX or department of a vPBX group. |
| Name & Info | | List of children groups of this group. | |

Configure Group Attribute:

New Group Attribute

Name

ZONE

Value

Public Zone

Ok

Save

Delete

Close

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|---|-------------------------------------|
| Name | Selection | | Defines the Group Attribute name. |
| Value | String | [empty Value, max. 256 char] Default: empty | Defines the value of the attribute. |

4.3.2 List of the Group Attributes

| Group Attribute | Description |
|--|--|
| ZONE | Refers to a Zone Profile "Key", which is configured in ConfigCenter > "System" > "Zone Profiles". It is used to differentiate the provisioning behavior of devices in distinct IP Zones. |
| anCsDomain | Defines "Cloud ID" of the "an IP-Phone". The "Cloud ID" defines the validity and GUI of the "an IP-Phone". |
| channels maxPrivate musicOnHold publicPrefix switchNight switchWeekend teamsDomain | Obsolete vPBX attributes |
| anSoftDomain | Deprecated |


5 The Customer "Account"

5.1 Introduction to the Central Function of the Account

In the anSwitch V6 the user or customer is represented in the "Account".

In the context of the anSwitch V6 nearly all user configuration eclipse the "Account"

- ▶ All configurations of an account are directly done in the menu "Account", e.g. the SIP credentials, or assigned via profiles, e.g. the routing table.
- ▶ An account is usually configured by an "Operator".



5.2 The Provider Defines the Usage of the Account

The anSwitch V6 doesn't know predefined types of accounts, e.g. residential, business or vPBX extensions! The different usage of the parameter configuration makes the difference.

The provider's marketing has to define and naming their offerings for their customers, for example:

| Offering Name | Max. Phone Numbers | Max. Channels | AdminCenter Access | VoiceMail | AN Phone APPs | ... |
|----------------------------|--------------------|---------------|--------------------|-----------|---------------|-----|
| "Residential User" | 1 | 2 | No | Yes | No | ... |
| "Power Residential" | 3 | 6 | Yes | Yes | Yes | ... |
| "Small Business SIP Trunk" | 10 | 6 | No | No | No | ... |
| "Business SIP Trunk" | 100 | 30 | No | No | No | ... |

The Operator must then configure the customer Account to meet the marketing offering and therefore the customer needs.


5.3 Use-Cases of a Customer Account

5.3.1 "Residential" Customer Account

The "Residential" customer Account may be characterized as follows:

- ▶ The customer wants to use the user telephony features offered by the anSwitch V6, e.g. call forwarding, VoiceMail Box, etc.
- ▶ The customer has a limited number of phone numbers.

- ▶ The customer's phones will individually register the phone number of the Account.



The information an Operator needs for configuring this type of Account:

- ▶ Basics:
 - ▶ Tenant
 - ▶ Customer ID
 - ▶ Customer info & Email address
 - ▶ Channel limitations
 - ▶ Emergency Location
- ▶ Routing & Rating:
 - ▶ Routing Table
 - ▶ Blocking ruleset
 - ▶ Pricelist
 - ▶ TopStop limitation
- ▶ Advanced:
 - ▶ Account valid from
- ▶ Addresses:
 - ▶ Telephone numbers
 - ▶ Voicemail Box & AdminCenter Access

Information that must be returned to the customer after the creation of the Account:

- ▶ SIP credentials:
 - ▶ Username & Password
- ▶ Telephone numbers:
 - ▶ Telephone numbers (confirmed)
- ▶ Registration domain:
 - ▶ Domain name or IP address
- ▶ Voicemail Box access:
 - ▶ PIN
- ▶ AdminCenter access:
 - ▶ URL
 - ▶ Username
 - ▶ Password

5.3.2 "Business" Customer Account


The "Business" customer Account may be characterized as follows:

- ▶ The customer has an own IP PBX which handles the user telephony features.
- ▶ The customer has many phone numbers, e.g. 100 numbers.
- ▶ The customer requires just the call routing from and to the PSTN.

In this use-case we have to distinguish between to cases:


1. The customer's SIP equipment can register on the anSwitch V6.
 - ▶ We need to define which is the main number the SIP equipment has to register.

- ▶ This type of use-case is easy to handle for an Operator and doesn't generate extra efforts.



- The customer's SIP equipment cannot register on the anSwitch V6.

- ▶ We need to configure a SIP-Trunk profile on the anSwitch V6 for interoperation with SIP equipment.
- ▶ This type of use case can lead to a great deal of effort, as the configuration of the SIP-Trunk profile can take a long time depending on the IP environment and customer requirements.



The information an Operator needs for configuring this type of Account:

- ▶ Basics:
 - ▶ Tenant
 - ▶ Customer ID
 - ▶ Customer info & Email address
 - ▶ Channel limitations
 - ▶ Emergency Location
- ▶ Routing & Rating:
 - ▶ Routing Table
 - ▶ Blocking ruleset
 - ▶ Pricelist
 - ▶ TopStop limitation
- ▶ Advanced:
 - ▶ Account valid from
 - ▶ Music on Hold MOH transparent
- ▶ Addresses:
 - ▶ Telephone numbers
 - ▶ Main number
- ▶ In case of the need of SIP-Trunk profile a project should be started for the evaluation of the configuration requirements of the SIP-Trunk profile.


Information that must be returned to the customer after the creation of the Account:

- ▶ SIP credentials:
 - ▶ Username & Password when the customer's SIP equipment can register.
- ▶ Telephone numbers:
 - ▶ Telephone numbers (confirmed)
 - ▶ Main number for registration
- ▶ Registration domain:
 - ▶ Domain name or IP address

6 Manage an Account



6.1 Variants of Managing an Account


An account can be managed by various ways:

- ▶ **ConfigCenter**
This is the main variant and offers all possibilities to configure an account and its parameters.
For details see below.
- ▶ **DAML API of the DataAccessCenter**
The DAML API allows configuring the account directly from a customer management system CMS.
For details see the manual "Manual DataAccessCenter DAML API".
- ▶ **AdminCenter**
Once an account is created a user can manage, configure and apply user features to the account. A user cannot create or delete the account and its phone numbers.
For details see the anSwitch V6 [AdminCenter online help](#) .

6.2 Managing and Configuring an Account Using the ConfigCenter


Log in to the ConfigCenter as Administrator or Operator:

- > Menu: Accounts
- > The dialog "Accounts" is displayed. It allows:
 - ▶ To create a customer Account, click icon .
 - ▶ Modify and delete a customer Account, click the row of the desired account.
 - ▶ Delete a customer Account click icon  or click the button "Delete" in the dialog "Account: ..."











6.3 Configuring the Account Parameters

6.3.1 Account Tab "Basic" Parameters






| Parameter Name | Data Type | Allowed Values | Description |
|----------------|----------------|--|--|
| Channels | Display & link | Channels 0 Channels ➡ | Displays the number of active connections of this Account. ➡ is the link to the list of active connection, details see "Display of Concurrent Calls of an Account" ↗. |
| Addresses | Display & link | Addresses 1 Address ➡ 🔑 | Displays the number of addresses (phone numbers) of this Account. ➡ is the link to the list of addresses, details see "Manage Addresses of an Account (Phone Numbers) Display of Concurrent Calls of an Account" ↗. 🔑 is the link to the list of address wizard, details see "Managing and Configuring an Address Using the ConfigCenter" ↗. |
| Call Forwards | Display & link | Call Forwards 1 Call Forward ➡ | Displays the number of call forwards of this Account. ➡ is the link to the list of call forwards, details see "Manage Call Forwards of an Account" ↗. |
| Attributes | Display & link | Attributes 1 Attribute ➡ | Displays the number of call forwards of this Account. ➡ is the link to the list of call forwards, details see "Manage the Attributes of an Account" ↗. |
| Tenant | Selection | [- (none) List of configured Tenants] Default: - (none) | Defines the owning tenant of the account. Note: ► The tenant must be configured on system level. If logged in as tenant Administrator/Operator, then the tenant value is given and cannot be changed. |
| Account Name | String | [empty Max. 32 char] Default: empty | Mandatory configuration! Defines a unique identification name of the account. Values: |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|--|---|
| | | | <p>► ?: A "?" character is a placeholder for a counting number.</p> <p>Example:</p> <ol style="list-style-type: none"> 1. Create the first account with name: test-???? 2. The created account will have assigned the name: test-0000 3. Create the next account with name: test-???? 4. The created account will have assigned the name: test-0001 |
| Info | String | [empty Max. 128 char] Default: empty | Any information about this account. |
| Username | String | [empty Max. 32 char] Default: empty | <p>Mandatory configuration!</p> <p>Defines the SIP username of the account. It must be used by all SIP devices that register to any SIP address of this account.</p> <p>Values:</p> <p>► ?: A "?" character is a placeholder for a random character.</p> <p>Example:</p> <p>► Create username: myname-????</p> <p>► The created username: myname-1ntA</p> |
| Password | String | [empty Max. 32 char] Default: empty | <p>Mandatory configuration!</p> <p>Defines the SIP password of the account. It must be used by all SIP devices that register to any SIP address of this account.</p> <p>Note: The value will never be displayed (a line of dots is displayed) and is stored encrypted in the database!</p> <p>Values:</p> <p>► ?: A "?" character is a placeholder for a random character.</p> <p>Example:</p> <p>► Create password, e.g.16 ?: ????????????????</p> <p>► The created password will have 16 random chars.</p> |
| Channels | Number | [empty ≥ 0 | <p>Determines how many concurrent connections are possible for this account.</p> <p>Note: Limiting the number of channels can also be seen as a security feature! In case of a fraud the fraudulent peer cannot open an unlimited number of concurrent connections.</p> |

| Parameter Name | Data Type | Allowed Values | Description |
|-------------------|----------------|--|--|
| | | | <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: No limitations ▶ 0: No channels → no incoming and outgoing connections are possible. ▶ ≥1: Exact number of possible channels for connections. |
| Location | Selection | [empty Emergency location] | <p>Assigns an emergency location to the account.</p> <p>This configuration defines the emergency call center to which an emergency call is forwarded.</p> <p>The emergency location is valid for all outgoing emergency calls from this Account. More specific emergency locations can be assigned for every phone number (Address) of the account.</p> <p>Search the available locations:</p> <ol style="list-style-type: none"> Type chars of the location and click the icon . Click the icon . <p>The dialog "Select emergency Location" opens and lists all available locations:</p> <ol style="list-style-type: none"> Type chars of the searched location. The list will become smaller. Finally select the desired location. Click button: Ok <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: The system-wide default emergency location is used. ▶ Emergency Location: The location name must be already configured in the emergency call configuration of this anSwitch V6. |
| Emergency Address | Display & link | Alpenstrasse 2b; 3072 Bern  | <p>Displays if the account has an associated Emergency Address according EU Regulations (NG112).</p> <p>Note: The implementation is according to the Swiss regulation.</p> <p> is the link to the linked Emergency Address, details see "Manage SIP-Trunk Profiles for SIP Equipment Communication" .</p> |
| SIP Trunks | Display & link | SIP Trunks 1 SIP Trunk  | <p>Displays if the Account has an associated SIP-Trunk Profile.</p> <p> is the link to the list of SIP-Trunk profiles, details see "Manage the Emergency Address" .</p> |

6.3.2 Account Tab "Routing & Rating" Parameters



| Parameter Name | Data Type | Allowed Values | Description |
|----------------|--|---|--|
| Routing Table | Selection | [empty List of RoutingTable] | <p>Assigns a RoutingTable to the account. A RoutingTable is necessary for routing calls to the PSTN.</p> <p>Note: Only allowed RoutingTables are displayed. For example, RoutingTables of other Tenants are not listed.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: For outgoing calls only OnNet connections are possible. ▶ RoutingTable: The RoutingTable name must be already configured in the routing configuration of this anSwitch V6. |
| Rulesets | Displays the number of selected RuleSets | 2 Active Rulesets  | <p>Defines the Rulesets that must be applied to this account.</p> <p>For assigning RuleSets click the icon :</p> <ul style="list-style-type: none"> ▶ The dialog "RuleSets for Account: ..." opens. ▶ Select the desired RuleSets. ▶ Click button: Ok <p>For checking the applied Rules of all RuleSets (there may be activated RuleSets on higher level) click button "Show selected Rules". This displays the dialog "Selected Rules of Account: ..." with all applied Rules that may influence incoming and outgoing calls from this account. This can be helpful in case of problem solving.</p> <p>Note: For checking the applied Rules of all RuleSets (there may be activated</p> |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------------|---|---------------------------------------|---|
| | | | <p>RuleSets on higher level) click button "Show selected Rules".</p> <p>This displays the dialog "Selected Rules of Account: ..." with all applied Rules that may influence incoming and outgoing calls from this account. This can be helpful in case of problem solving.</p> |
| Pricelist | Selection | [- (none) List of Pricelists] | <p>Assigns a user pricelist to the account.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: No call rating. ▶ Pricelist: The price list name must be already configured in the price list configuration of this anSwitch V6. <p>Note: No TopStop security is possible if no price list is assigned to the account!</p> |
| Advice of Charge AoC | String | [None AOC-D] Default: None | <p>Deprecated!</p> <p>Activate sending advice of charge AOC to all SIP devices registered to the account.</p> |
| TopStops | Displays the number of created TopStops | 2 TopStops ➡ | <p>Defines the TopStops that are assigned to this account.</p> <p>TopStop can be used:</p> <ul style="list-style-type: none"> ▶ For realizing a prepaid offering. ▶ As security feature! In the case of fraud, it can limit the financial damage for the customer. <p>➡ is the link to the list of account's TopStop, details see "Account TopStop" ↗.</p> |

6.3.3 Account TopStop

Manage TopStop as Administrator/Operator:

-
- > Menu: Accounts at Tab "Routing & Rating"
 - > Click button ➡ at Active Rulesets ➡
 - > The dialog "TopStops of Accounts" is displayed. It allows:
 - ▶ To check all active TopStop of this account
 - ▶ To create a new TopStop, click icon ➕
 - ▶ Modify a TopStop, click the row of the desired TopStop.
 - ▶ Delete a TopStop click icon ✖ or click the button "Delete" in the dialog "TopStop of Account: ..."
-

Example dialog "TopStops of Account" with the list of all configured TopStops:

TopStops of Account: ACC_Test-0000

Account: (* or ? as wildcards)

Address: (* or ? as wildcards)

State:

Page 1 of 1 (1 Entry) Search

| Access | Account | Address | State |
|--------|---------------|---------|---|
| System | ACC_Test-0000 | - | ● ✖ |

Close

Configuration dialog for a TopStop of an Account:

TopStop for Account: aan1-demo-training

Access:

Account:

Address:

Monitor Charge:

Maximum Charge: Fr.

Current Charge: Fr.

Remaining Charge: Fr.

Monthly Reset: ☒

Alarm Level:

Alarm E-mail:

Daily TopStop:

Daily Maximum Charge: Fr.

Daily Current Charge: Fr.


Daily Remaining Charge: Fr.

Ok Save Delete Close

| Property Name | Data Type | Allowed Values | Remark |
|---------------|-----------|---|---|
| Access | Selection | [- (none) System Account Address] Default: - (none) | <p>Defines the 3 types of TopStop objects that can be assigned to an account.</p> <p>Values:</p> <p>System: This TopStop is usually defined by a system administrator/operator or tenant operator.</p> <p>→ Use this type of TopStop for "hidden" TopStops that cannot be changed by a customer or user.</p> <p>→ In the ConfigCenter it is visible for administrators and operators.</p> <p>→ In the AdminCenter this TopStop is not visible.</p> <p>Account: This TopStop is usually defined by a tenant operator.</p> <p>→ A customer may see this configuration in the ConfigCenter and may modify it.</p> <p>→ In the ConfigCenter it is visible for system administrators/operators and tenant administrators/operators.</p> <p>→ In the AdminCenter this TopStop is not visible.</p> |

| Property Name | Data Type | Allowed Values | Remark |
|------------------------|--------------------------|---|---|
| | | | <p>Address: This TopStop is usually defined by a tenant operator or user. It will be applied to individual addresses of the account.</p> <p>→ In the ConfigCenter it is visible for system administrators/operators and tenant administrators/operators.</p> <p>→ In the AdminCenter this TopStop is visible for users.</p> |
| Account | Selection | [- (none) Name of the account] Default: - (none) | Defines that this TopStop is valid for the whole account. |
| Address | Selection | [- (none) List of configured addresses] Default: - (none) | Defines that this TopStop is valid for the selected address of this account. |
| Monitor Charge | Selection | [active inactive] Default: active | Defines if the TopStop is active or not. |
| Maximum Charge | Float | [empty value ≥ 0.0] Default: empty | <p>Defines the blocking limit per month for the account. It may not be exceeded by the charging sum of all connections of this account.</p> <p>If set to "empty" then no blocking limit is supervised.</p> |
| Current Charge | Float | | Display of the current sum of charges. |
| Remaining Charge | Float | | Display of the remaining sum. |
| Monthly Reset | <input type="checkbox"/> | Activate Default: Activated | <p>If activated it defines that the monthly maximum limit is reset at the start of a new month.</p> <p>Note: If not activated, the maximum charge can be interpreted as prepaid charge.</p> |
| Alarm E-mail | Email Address | [empty Max. 128 char] Default: empty | <p>If configured it defines the email address where this TopStop information is sent to when any limit is reached:</p> <ul style="list-style-type: none"> ▶ Alarm limit. ▶ Block limit |
| Alarm Level | Selection | [No 10 20 ... 90 100] Default: No | Defines the alarming limit in percent of the max. blocking limit where an alarm-email must be sent. |
| Daily TopStop | Selection | [active inactive] Default: inactive | Defines if the daily TopStop is active or not. |
| Daily Maximum Charge | Float | [empty value ≥ 0.0] Default: empty | <p>Defines the blocking limit per day for the account. It may not be exceeded by the charging sum of all connections of this account.</p> <p>If set to "empty" then no blocking limit is supervised.</p> |
| Daily Current Charge | Float | | Display of the current daily sum of charges. |
| Daily Remaining Charge | Float | | Display of the remaining daily sum. |

6.3.4 Account Tab "Advanced"






| Parameter Name | Data Type | Allowed Values | Description |
|-------------------------|---------------------|--|--|
| Valid from | YYYY/MM/DD hh:mm | [empty Date/Time] Default: empty | Defines the date/time of the activation of the account (and its addresses). Values: <ul style="list-style-type: none"> ▶ empty: The account is activated. ▶ Date/Time: The account is activated beginning at Date/Time. |
| until | YYYY/MM/DD hh:mm | [empty Date/Time] Default: empty | Defines the date/time of the deactivation of the account (and its addresses). Values: <ul style="list-style-type: none"> ▶ empty: The account is activated. ▶ Date/Time: The account is deactivated beginning at Date/Time. |
| Special Arrangement | Selection | [No Yes] Default: No | If activated, then the call control will not execute the caller identification check for all outgoing calls to the PSTN. Note: The caller identification check is usually enforced by law. Check the consequences if activated. |
| Alarm On Expiry | Selection | [No Yes] Default: No | If activated, the call control generates a monitoring alarm when no SIP-device is re-registering to the account. Note: This is a support measure that can be used if a real-time alarm is required to investigate why a SIP-device can't re-register again. |
| Use always Media Server | Selection | [No Yes] Default: No | If activated, the call control forces the peers of a connection to send their media streams via a MediaServer of the anSwitch V6. |


| Parameter Name | Data Type | Allowed Values | Description |
|---------------------------|-----------|---|--|
| | | | Note: This can be used as support measure to investigate QoS problems during a connection. |
| Music on Hold Transparent | String | [No Yes] Default: No | If activated, then the Music on hold of an e.g. IP-PBX is sent transparently to the peer device on hold. Else the standard hold music of the anSwitch V6 is sent. |
| Force Call ID (MCID) | String | [true false] Default: false | If activated, the call control will enforce to display the caller id of an incoming call even when the call was anonymous. Note: The application of MCID may be regulated by law. Check the consequences if activated. |
| Network(s) | String | [empty Max. 128 char] Default: empty | Defines whitelisted IP subnets from where a SIP-device is allowed to register to this account. Values: <ul style="list-style-type: none"> ▶ empty: No limitations ▶ List: Comma separated list of IP subnets, e.g.: 0.10.10.0/24, 192.168.0.0/22 |
| SIP Profile | Selection | [- (none) List of configured SIP-Profiles] Default: - (none) | Defines a prepared SIP-Profile with whitelisted IP subnets from where SIP-device is allowed to register to this account. |

6.4 Display of Concurrent Calls of an Account

Active connections of an account are displayed in the "Channels" list. The numbers of the caller and called party as well as the actual duration of the connection are displayed. The list is updated periodically. Administrators/Operators with sufficient authorization can actively terminate connections!

Log in to the ConfigCenter as Administrator or Operator:

- > Menu: Accounts
 - > Click at 0 Channels  the icon 
 - > The dialog "Channels of Account: ..." is displayed.
 - ▶ It displays:
 - ▶ Direction: Outgoing and incoming channels of a connection
 - ▶ Number: Calling number
 - ▶ Peer: Called number
 - ▶ State: State of the call
 - ▶ Delete a connection, click icon 



7 Manage Addresses of an Account (Phone Numbers)

7.1 Variants of Managing Addresses

An address can be managed by various ways:

- ▶ **ConfigCenter**
This is the main variant and offers all possibilities to configure an address and its parameters.
For details see below.
- ▶ **DAML API of the DataAccessCenter**
The DAML API allows configuring the addresses of an account directly from a customer management system CMS. For details see the manual "Manual DataAccessCenter DAML API".
- ▶ **AdminCenter**

Addresses cannot be managed via the AdminCenter.

7.2 Managing and Configuring an Address Using the ConfigCenter

For managing addresses a customer account must already be created.





Addresses can then be added, modified or deleted:

- ▶ Single addresses can be managed, see "Manage a Single Address"
- ▶ A range of addresses can be managed with the address wizard, see "Manage an Address Range with the Address Wizard".

7.2.1 Manage a Single Address

Adding a new address to an account or managing an existing one, Log in to the ConfigCenter as Administrator or Operator.

Add a new address:

-
- > Menu: Accounts
 - > Search for the account the new address must be added.
 - > Click the icon  at **Addresses**  **0 Addresses**
 - > The dialog "Addresses of Account: ..." is displayed. It allows:
 - ▶ To create a new address, click icon 
 - ▶ Modify and delete an address, click the row of the desired address.
 - ▶ Delete an address click icon  or click the button "Delete" in the dialog "Address: ..."
-



Manage an existing address:

-
- > Menu: Addresses
 - > The dialog "Addresses" is displayed.
 - > Search for the address that must be managed.
 - > Click the row of the desired address
 - > The dialog "Address: ..." is displayed. It allows to:
 - ▶ Modify the address parameters.
 - ▶ Delete the address, click the button "Delete".
-


7.2.2 Manage an Address Range with the Address Wizard

Adding a new address range to an account or managing range, Log in to the ConfigCenter as Administrator or Operator.

Add a new address range or manage an existing range:

- > Menu: Accounts
 - > Search for the account the address range must be managed.
 - > Click the icon  at Addresses 1 Address 
 - > The address wizard dialog "Address Wizard for of Account: ..." is displayed. It allows:
 - ▶ To create new addresses
 - ▶ To modify addresses
 - ▶ To delete addresses,
 - > Select the action to be done.
 - > Define the addresses to be managed.
 - > Click the button: Next >
 - > Follow the instructions of the wizard:
 - ▶ For action "Create": Configure the desired parameter.
 - ▶ For action "Modify": Select the parameter and configure the new value.
 - ▶ For Action "Remove": Define the addresses.

Select the action to be done:




| Parameter Name | Data Type | Allowed Values | Description |
|------------------|-----------|---|---|
| Action | Selection | [Create Modify Remove] Default: Create | Defines what has to be done with the defined addresses in parameter "Number Selection". Values: <ul style="list-style-type: none"> ▶ Create: The defined addresses will be created. ▶ Modified: The defined addresses will be modified. ▶ Remove: The defined addresses will be deleted. |
| All Numbers | Selection | [No Yes] Default: No | Specifies for the "Modify" and "Remove" actions whether all addresses in the account or only the addresses listed in "Number Selection" should be taken into account. Values: <ul style="list-style-type: none"> ▶ No: Just the listed addresses will be considered. ▶ Yes: All addresses will be considered. |
| Number Selection | String | [empty Max. 128 char] Default: empty | Defines the addresses to be managed. Values: <ul style="list-style-type: none"> ▶ empty: No addresses are managed. ▶ Addresses: Defines single addresses. Single addresses and ranges must be comma separated. |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|----------------|--|
| | | | Example: 0222,0330-9,0400-99,0555 Will create or manage the: <ul style="list-style-type: none"> ▶ Single numbers 0222 and 0555 ▶ The 10 addresses range 0330, 0331, ..., 0339 ▶ The 100 addresses range 0400, 0401, ..., 0499 |

For action "Create": Configure the desired parameter:

- ▶ Configure the desired parameter values (see "Configuring the Address Parameter")



Address Wizard for Account: ACC_Test-0000

Number Selection: 0222,0330-9,0400-99,0555

Domain: .com

Display Name:

Presentation:

Valid from:

Valid until:

Outported to:

Language: Deutsch

Registers via Main Number: No

Multiple registrations: Weighted

Signaling only: No

Incoming Only: No

Disabled: No

On Busy: Call waiting, busy if one device rejects

AdminCenter Access: No Password:


Language: English

Fill in the form and press "Next >" to continue; To select another Range press "< Previous"

< Previous Next > Close

For action "Modify": Select the parameter and configure the new value.

- ▶ For example, for all addresses of the account:



Address Wizard for Account: ACC_Test-0000

Action: Modify

All numbers: Yes

Number Selection:

Domain: .com

Display Name:

Presentation:

Valid from:

Valid until:

Outported to:

Language: English

Registers via Main Number: No

Multiple registrations: Weighted

Signaling only: No

Incoming Only: No

Disabled: No

On Busy: Call waiting, busy if one device rejects

AdminCenter Access: No Password:


Language: English

Fill in the form and press "Next >" to continue; To select another Range press "< Previous"

< Previous Next > Close

For Action "Remove": Define the addresses.

- ▶ Define the addresses to be deleted.



Address Wizard for Account: ACC_Test-0000

Action: Remove

All numbers: No

Number Selection: 0400-99,0556

Configure Virtual PBX: ☐

Configure Answering Machine: ☐


Configure MGCP: ☐


The address wizard will execute the action when all given data are valid:

- ▶ If there are problems the wizard will notify it with a notification dialog.
- ▶ Execution details and the position where a problem raised can be checked in the log → click button: Details ...



Address Wizard for Account: ACC_Test-0000

 Data is valid and can be saved




Press "Next >" to save the Data or "< Previous" to change.

Details... < Previous Next > Close

7.3 Configuring the Address Parameters

7.3.1 Address Tab "Basic" Parameters



Address: 02233445566

Registration: No Registrations

Account: ACC_Mickey_Mouse

TopStops: 0 TopStops

Basic | Advanced | Answering Machine | Virtual PBX

Number: 02233445566

Domain: .com

Display Name: Mickey Mouse

Department: -

Presentation: -

Language: English

Address Type: Normal

Routing over main registration: No






Location:


Emergency Address: unknown

Ok Save Delete Close


| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|--|--|
| Number | Number | [empty Max. 128 char] Default: empty | Mandatory configuration! Defines the phone number part of the SIP address. |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|--|--|
| Domain | String | [empty Domain name, max. 128 char IP address] Default: empty | Mandatory configuration! Defines the domain part of the SIP address. This is usually the domain name or IP address of the virtual public IP address of the anSwitch V6 . Values: <ul style="list-style-type: none"> ▶ empty: Not allowed. ▶ Domain name: Domain name ▶ IP address: IP address |
| Display Name | String | [empty - Display, max. 64 char] Default: empty | Defines the display part of the SIP address. Values: <ul style="list-style-type: none"> ▶ empty: The transferred display information is not touched. ▶ -: The transferred display information is deleted. ▶ Display: The transferred display information is replaced with this string. |
| Department | Selection | [empty List of configured departments of a vPBX] Default: empty | Deprecated! Defines the vPBX department this private vPBX number belongs to. |
| Presentation | Selection | [empty Show Hide] Default: empty | Defines whether the outgoing call from this address is signaled anonymous to the peer or not. Values: <ul style="list-style-type: none"> ▶ empty: The presentation is transferred as it is received from the registered SIP device. ▶ Show: The presentation is activated in any case. ▶ Hide: The presentation is deactivated in any case. |
| Language | Selection | [English Deutsch Français Italiano] Default: English | Defines the language of: <ul style="list-style-type: none"> ▶ The in-band notifications, e.g. of do not disturb. ▶ VoiceMail Box notifications |
| Address Type | Selection | [Normal Main Number | Defines how this address must be used. |

| Parameter Name | Data Type | Allowed Values | Description |
|--|-----------|--|---|
| <p>Registering and incoming routing of different tel. number types:</p> <p>► Behavior "Normal Number":</p>  <p>► Behavior "Main Number":</p>  <p>► Behavior "Base Number":</p>  | | <p>Base Number Preferred Number]</p> <p>Default: Normal</p> | <p>Values:</p> <ul style="list-style-type: none"> ► Normal: Defines that a SIP device has to register to this number. The call control needs the registration information to route incoming calls to this number. ► Main Number: This number is used for the registration of all numbers in this account which are tagged "Yes" at parameter "Routing over main registration". ► Base Number: Defines a number prefix for routing incoming calls with matching numbers toward the main number. |
| | | | <ul style="list-style-type: none"> ► Preferred Number: Defines that this number is used in the SIP Header "From" or "P-Preferred" for all outgoing calls from this account. <p>Note:</p> <ul style="list-style-type: none"> ► There is only one main number allowed per account! ► "Normal" numbers and a range of numbers which are registered via a "Main" number can be mixed within an account. |
| | | | |
| Routing over main registration | Selection | <p>[No Yes]</p> <p>Default: No</p> | <p>Defines id this address is registered automatically, when the main number of this account has a registered SIP-device.</p> <p>Values:</p> <ul style="list-style-type: none"> ► No: The address is not concurrently registered with the main number. ► Yes: The address is concurrently registered with the main number. |
| Location | Selection | <p>[empty Emergency location]</p> <p>Default: empty</p> | <p>Assign a specific emergency location to the Address.</p> <p>This configuration defines the emergency call center to which an emergency call is forwarded.</p> <p>The emergency location is valid for all outgoing emergency calls from this Address.</p> <p>Search the available locations:</p> <ol style="list-style-type: none"> 1. Type chars of the location and click the icon . 2. Click the icon . <p>The dialog "Select emergency Location" opens and lists all available locations:</p> <ol style="list-style-type: none"> 1. Type chars of the searched location. |

| Parameter Name | Data Type | Allowed Values | Description |
|-------------------|----------------|------------------------------|---|
| | | | 2. The list will become smaller. 3. Finally select the desired location. 4. Click button: Ok Values: ▶ empty: The account emergency location is used. ▶ Emergency Location: The location name must be already configured in the emergency call configuration of this anSwitch V6. |
| Emergency Address | Display & link | Alpenstrasse 2b; 3072 Bern ➔ | Displays if the Address has an associated Emergency Address according EU Regulations (NG112). Note: The implementation is according to the Swiss regulation. ➔ is the link to the linked Emergency Address, details see "Manage SIP-Trunk Profiles for SIP Equipment Communication"  . |

7.3.2 Address Tab "Advanced" Parameters



Address: 0222 

Registration No Registrations ➔

Account ACC_Test-0000 ➔

TopStops 0 TopStops ➔

Basic **Advanced** Answering Machine Virtual PBX

Valid from  until 

Outported to

Multiple registrations Weighted ▾

Signaling only No ▾

Incoming only No ▾

Disabled No ▾

On Busy Call waiting, busy if one device rejects ▾

Mobile Number




Ring only on SIP Phone if possible No ▾

AdminCenter Access ☐ ➔


Ok Save Delete Close

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|---------------------|--|--|
| Valid from | YYYY/MM/DD hh:mm | [empty Date/Time] Default: empty | Defines the date/time of the activation of this address. Values: ▶ empty: The address is activated. ▶ Date/Time: The address is activated beginning at Date/Time. |
| until | YYYY/MM/DD hh:mm | [empty Date/Time] Default: empty | Defines the date/time of the deactivation of the account (and its addresses). Values: ▶ empty: |

| Parameter Name | Data Type | Allowed Values | Description |
|------------------------|-----------|---|--|
| | | | <p>The address is activated.</p> <ul style="list-style-type: none"> ▶ Date/Time: The address is deactivated beginning at Date/Time. |
| Outported to | String | <p>[empty Max. 50 char]</p> <p>Default: empty</p> | <p>Used in Switzerland only!</p> <p>Defines a specific number prefix for outported numbers.</p> <p>When additionally a valid "until" date/time is set and an outported prefix is configured then incoming calls to this number are re-routed back into the PSTN.</p> <p>Note: Mostly it is a PSTN number prefix of the new PSTN carrier of this number.</p> |
| Multiple registrations | Selection | <p>[Weighted Yes No]</p> <p>Default: Weighted</p> | <p>Defines how many SIP-devices are allowed to register.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ Weighted: An unlimited number of SIP devices are allowed to register. Outgoing calls toward the registered devices are made according to the requested weighting. ▶ Yes: An unlimited number of SIP devices are allowed to register. ▶ No: Only on SIP device is allowed to register. |
| Signaling only | Selection | <p>[No Yes]</p> <p>Default: No</p> | <p>If set to "Yes" only outgoing calls are allowed for SIP devices registered to this number.</p> |
| Incoming only | Selection | <p>[No Yes]</p> <p>Default: No</p> | <p>If set to "Yes" only incoming calls are allowed for SIP devices registered to this number.</p> |
| Disabled | Selection | <p>[No Yes]</p> <p>Default: No</p> | <p>If set to "Yes" no incoming or outgoing calls are allowed for this number.</p> <p>Note: This number belongs to this account. It cannot be a valid number in any other account on this Aarenet VoIP Switch.</p> |
| On Busy | Selection | <p>[Call waiting, busy if one device rejects Call waiting, busy if all devices reject Signal busy]</p> <p>Default: Call waiting, busy if one device rejects</p> | <p>Defines what a caller will hear when this number is already in an active call.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ Call waiting, busy if one device rejects: All registered SIP devices are signaled with the new incoming call. If one device is rejecting the new call, then the caller hears the busy tone. ▶ Call waiting, busy if all devices reject: All registered SIP devices are signaled with the new incoming call. If all SIP devices are |

| Parameter Name | Data Type | Allowed Values | Description |
|------------------------------------|--------------------------|--|---|
| | | | rejecting the new call, then the caller hears the busy tone. <ul style="list-style-type: none"> ▶ Signaling Busy: Immediately rejects the new incoming call (no call waiting) when one device is busy. The caller hears the busy tone. |
| Mobile Number | Number | [empty Number, max. 128 char] Default: empty | Defines any type of telephone number that will be signaled in parallel to this address for an incoming call. Values: <ul style="list-style-type: none"> ▶ empty: Signaling not active. ▶ Number: Defines the parallel called number. |
| Ring only on SIP Phone if possible | Selection | [No Yes] Default: No | If set to "Yes" incoming calls are only signaled when a SIP device is registered. This may be needed if a SIP equipment is connected with a SIP-trunk. |
| AdminCenter Access | <input type="checkbox"/> | AdminCenter Access   Activate Default: Not activated | If activated, then it is possible to configure an AdminCenter user access for this number. Click  for configuring the AdminCenter address administrator, see below ↗ . |

7.3.3 AdminCenter Account Dialog "Address Administrator" Parameters



| Parameter Name | Data Type | Allowed Values | Description |
|-----------------|-----------|--|--|
| Number | | | Display of the address this AdminCenter address administrator belongs. |
| My Username | String | [empty Max. 128 char] Default: empty | Defines the username for this AdminCenter account. |
| My Password | String | [empty Max. 128 char] Default: empty | Defines the password for this AdminCenter account. |
| Verify Password | String | | Re-enter the password for check. |

| Parameter Name | Data Type | Allowed Values | Description |
|------------------------------|---------------|---|---|
| Renew Password | Selection | [No Yes] Default: Yes | If set "Yes", defines that the user upon the very first login is forced to change the password. |
| Language | Selection | [English German Vietnamese] Default: English | Defines the language of the ConfigCenter configuration pages. |
| E-Mail Address | Email Address | [empty Max. 128 char] Default: empty | Defines the email address where password recovery information for the AdminCenter is sent to. |
| Access Networks | String | [empty Max. 128 char] Default: empty | Defines whitelisted IP subnets from where a user is allowed to access the AdminCenter. Values: <ul style="list-style-type: none"> ▶ empty: No limitations ▶ List: Comma separated list of IP subnets, e.g.: 10.10.10.0/24, 192.168.0.0/22 |
| WEB Profile | Selection | [- (none) List of configured SIP-Profiles] Default: - (none) | Defines a prepared WEB-Profile with white-listed IP subnets from where a user is allowed to access the AdminCenter. |
| Login is blocked | Selection | [No Yes] Default: No | Displays if the AdminCenter account is blocked by too many unsuccessful login attempts. Deblock the account by selecting "Yes" |
| Two Factor Authentication | | | Defines the user authentication against a LDAP service. ➔ Check with the Aarenet support for configuration. |
| LDAP Authentication | | | |
| LDAP Authentication Template | | | |
| LDAP Authentication URL | | | |
| LDAP Authentication secure | | | |

7.3.4 Address Tab "Answering Machine" (VoiceMail Box) Parameters

See chapter "Manage the VoiceMail Box of an Address" [↗](#).

7.3.5 Address Tab "Virtual PBX" Parameters

The feature vPBX is deprecated and is not describes anymore in the anSwitch V6 manuals.

8 Manage the VoiceMail Box of an Address

8.1 Overview of the Usage of a VoiceMail Box


The personal VoiceMail Box answers automatically incoming calls and a caller may leave a message or send a FAX:

- ▶ A VoiceMail Box is associated with an address (phone number).
 - ▶ An Administrator/Operator must activate the VoiceMail Box via the ConfigCenter and may execute its initial configuration.
 - ▶ A user can manage the VoiceMail Box via the AdminCenter or any phone that is connected to the address.
- ▶ For recording messages or Fax an Administrator/Operator or the user must configure a Call Forward to the VoiceMail Box.
- ▶ Received messages:
 - ▶ Can be listened to from any phone that is connected to the address by using the *#-procedure *86 .
 - ▶ Can be sent as audio file as an attachment of an email.
 - ▶ Can be managed and listened to via the user's AdminCenter account.
- ▶ Received Fax:
 - ▶ Can be sent as PDF-formatted file as an attachment of an email.

8.2 Configuring the VoiceMail Box Parameters via ConfigCenter

Manage a VoiceMail Box of an address as Administrator/Operator:

- > Menu: Addresses
 - > The dialog "Addresses" is displayed.
 - > Search for the address whose VoiceMail Box must be managed.
 - > Click the tab "Answering Machine":
 - > Modify the VoiceMail Box parameters.



| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|---|--|
| Active | Selection | [No Yes] Default: No | If set "Yes", defines that the VoiceMail Box is active for this address. |
| New Password | Number | [empty PIN, max. 32 digits] Default: empty | Defines the PIN to be used for accessing the VoiceMail Box. Values: ▶ empty: |

| Parameter Name | Data Type | Allowed Values | Description |
|------------------------|--------------------------|---|--|
| | | | <p>No PIN defined, so no PIN is needed for the VoiceMail Box access.</p> <ul style="list-style-type: none"> ▶ PIN: Number |
| Verify New Password | Number | | Re-enter the PIN for check. |
| E-Mail Address | Email Address | <p>[empty Max. 128 char]</p> <p>Default: empty</p> | Defines the email address where messages or Fax will be sent. |
| Login without Password | Selection | <p>[No Yes]</p> <p>Default: No</p> | <p>If set "Yes", defines whether the PIN is needed when the VoiceMail Box is accessed from any phone registered to this account.</p> <p>Note: The PIN is always requested from any access other than the "own" phones.</p> |
| Signaling | Selection | <p>[Only explicit MWI subscriptions Implicit, all registered devices Never]</p> <p>Default: Only explicit MWI subscriptions</p> | <p>Defines whether and how the phone is informed about a new message in its VoiceMail Box. The format is „Message Waiting Information MWI“.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ Only explicit MWI subscriptions: Defines Explicit MWI Subscription only! MWI messages are sent to the phone when it prior subscribed for the WMI service. ▶ Implicit, all registered devices: A MWI message is automatically sent to all phones registered to this address. The phone must not subscribe to the WMI service. ▶ Never: No WMI message is sent. |
| Type | Selection | <p>[Automatic Voice only Fax only]</p> <p>Default: Automatic</p> | <p>Defines which type of information the VoiceMail Box records.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ Automatic: Both caller messages and Fax transmissions are recorded. ▶ Voice only: Only caller messages are recorded. ▶ Fax only: Only Fax transmissions are recorded. |
| Format | Selection | <p>[wav mp3]</p> <p>Default: wav</p> | Defines the audio format a caller message is recorded. |
| Blocked | <input type="checkbox"/> | <p>Activate</p> <p>Default: Not activated</p> | <p>Displays if a VoiceMail Box is blocked after many failed logins.</p> <p>It can be manually de-blocked or blocked.</p> |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------------------------|--------------------------|------------------------------------|--|
| Delete message after E-Mail sent | <input type="checkbox"/> | Activate Default: Not activated | Defines that the VoiceMail Box deletes a message or Fax after it is sent to the defined email address. Note: An email address must be configured. |
| Send E-Mail without message | <input type="checkbox"/> | Activate Default: Not activated | Defines that also a message is sent when a caller doesn't leave a message. |
| State | | | Displays the number of recorded messages. |

9 Manage Call Forwards of an Account

9.1 Overview of a Call Forward CF

The feature "Call Forward CF" enables incoming calls to an account to be routed toward a new destination upon definable conditions.

The anSwitch V6 offers sophisticated configuration options for call forwards:

Different execution types of CF:



- ▶ Call forward unconditional CFU
- ▶ Call forward busy CFB
- ▶ Call forward rejected CFR
- ▶ Call forward no reply CFNR
- ▶ Call forward fall back CFF
- ▶ Call forward reject CFR
- ▶ Call fork CFO
- ▶ Special cases:
 - ▶ Call redirection REDIR
- ▶ Call forward are executed according to their defined priority.
- ▶ The condition for executing a call forward can be made depending on:
 - ▶ Caller SIP address.
 - ▶ Called SIP address.
 - ▶ The number presentation (e.g. anonymous call) is defined by the calling side.
 - ▶ Java regular expression can be applied.
- ▶ The forwarding destination can be:
 - ▶ Any dialable phone number
 - ▶ Any SIP address
 - ▶ Any VoiceMail Box
 - ▶ etc.
- ▶ Call forwarding can be scheduled to be active during:
 - ▶ Daily periods
 - ▶ Weekdays


Call forward can be activated and configured by:

- ▶ The Administrator/Operator in the ConfigCenter
- ▶ The user in the AdminCenter
- ▶ The user with *#-procedures on a phone which is registered to the account.


9.2 Managing and Configuring a Call Forward Using the ConfigCenter

Manage Call Forward of an account in the ConfigCenter as Administrator/Operator:

-
- > Menu: Accounts
 - > The dialog "Accounts" is displayed.
 - > Click the row of the desired account.
 - > Click the icon  at Call Forwards 0 Call Forwards 
-



9.3 Configuring the Call Forward Parameters





| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|--|--|
| Name | String | [empty Max. 128 char] Default: empty | <p>Defines the name of this call forward.</p> <p>When the call forward was created via AdminCenter then no name is given.</p> <p>When the call forward was created by a user with a *#-procedure the name is created as follows, e.g.:</p> <p>(*2108877665544-0123456789))</p> <p>(*2108877665544-0123456789)</p> <p>CF service that has activated. New destination For which number of this account this CF is valid.</p> |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|---|---|
| Type | Selection | <p>[CFU: Call forward unconditional CFB: Call forward busy CFNR: Call forward no reply CFF: Call forward fall back CFR: Call forward reject CFO: Call fork DIST: Call distribution REDIR: Call redirection]</p> <p>Default: CFU: Call forward unconditional</p> | <p>Defines the type of the call forwarding CF.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ CFU: Call Forward Unconditional The call forwarding is executed in any case. ▶ CFF: Call Forward Fallback The call forward is executed if no valid SIP device registration is active for an account. ▶ CFB: Call Forward Busy The call forwarding is executed if the user is busy with another call. ▶ CFR: Call Forward Rejected This call forwarding is executed when the call is rejected by a user. ▶ CFNR: Call Forward No Reply The call forwarding is executed if within a specified period of time the call is not answered by the called party. ▶ CFO: Call Fork This call forwarding defines a second destination telephone number to be called upon an incoming call. <p>Special call forwards:</p> <ul style="list-style-type: none"> ▶ REDIR: Call Redirection This call forward defines the RFC compliant "SIP 302 Redirect Temporarily". If a called destination rejects with "302 Redirect Temporarily" then the call is forwarded to the defined destination of the call forward. <p>Outdated call forwards:</p> <ul style="list-style-type: none"> ▶ DIST: Call Distribution A "Call Distribution" allows in a vPBX complex call forwarding to different destinations. |
| Priority | Integer | <p>[- (none) ≥ 1]</p> <p>Default: - (none)</p> | <p>Defines the priority of the call forward execution.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ 1: Highest priority. <p>Call Forwards and Call Rejects configured by the user via the AdminCenter or *#-procedures have fixed priorities:</p> <ul style="list-style-type: none"> ▶ Any Call Forward: Prio 10 ▶ Do not Disturb: Prio 11, 12 ▶ Reject Anonymous calls: Prio 8, 9 |
| Ringing Delay | Integer | Number of seconds | Defines with the call forward type "CFNR: Call Forward No Reply" the delay until the call forward destination is called. |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|---|--|
| Pattern: | | <p>The call forward is executed when the whole defined calling SIP address pattern matches:</p> <p>Pattern</p> <div> Destination " <input type="text"/> 012.* @ <input type="text"/> Source " <input type="text"/> 0041.* @ <input type="text"/> Presentation <input type="text"/> Hide ▾ </div> <p>The destination (called side), source (calling side) and calling side presentation can be combined. The combination acts as logical AND function.</p> | |
| Destination | String | [empty Max. 128 char of the whole SIP address] Default: empty | Defines the SIP address pattern of the dialed destination SIP address that must match. <div>"Home Office" 0123456789 @home.com</div> <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: No check of the SIP address part. ▶ SIP Address parts: Defines the display, number and domain pattern. <p>Note: Java Regex patterns are allowed¹.</p> <div>" <input type="text"/> 012.* @ <input type="text"/></div> |
| Source | String | [empty Max. 128 char of the whole SIP address] Default: empty | Defines the SIP address pattern of the calling SIP address that must match. <div>" <input type="text"/> 0041.* @ <input type="text"/></div> <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: No check of the SIP address part. ▶ SIP Address parts: Defines the display, number and domain pattern. <p>Note: Java Regex patterns are allowed.</p> |
| Reject Pattern | String | [empty String max. 128 char] Default: empty | Defines an optional call reject information of the CF type "CFR: Call forward reject". This information is returned to the caller. |
| Presentation | Selection | [empty Show Hide] Default: empty | Defines how the calling number presentation shall be considered for the call forwarding. <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: No check of the caller presentation. ▶ Show: The caller defined that the calling SIP address is presented. ▶ Hide: The caller defined that the calling SIP address must not be presented. → Defines an anonymous call. |

¹ [Java Regex](#) documentation

| Parameter Name | Data Type | Allowed Values | Description |
|--|--------------------------|--|---|
| <i>Forward to:</i> | | | |
| Destination | String | [empty - Number, max. 128 char of the whole SIP address] Default: empty | Defines the SIP address pattern of the call forwarding destination.  Values: <ul style="list-style-type: none"> ▶ empty: The original value of the SIP address is not replaced. ▶ - : The original value of the SIP address is deleted. ▶ Number: New value of the SIP address that defines the call forwarding destination. |
| <i>Schedule:</i> | | | |
| Active | Selection | [During Periods Outside Periods] Default: During Periods | Defines at which day time periods the call forward shall be active or not active. |
| Period 1 ... until ... Period 2 ... until ... | hh:mm | Hours & minute in 24h notification Default: empty | Defines at which day time periods the call forward shall be active or not active. Example:  If no weekday is selected, then the call forward is active every day. |
| Monday - Sunday | <input type="checkbox"/> | Activate Default: Not activated | Defines the weekdays the call forward shall be active. If no time periods are configured, then the call forward is active all day (24 hours). |

9.4 Examples of Call Forwarding

Example: CF to 08877665544 for any telephone number of the account.

Pattern

Destination " " @ "

Source " " @ "

Presentation ▼

Forward to

Destination " " 08877665544 @ "

No, matching pattern!

New destination tel. number.



Example: CF to 08877665544 for telephone number 0123456789 of the account.

Pattern

Destination " 0123456789 @

Source " " @

Presentation

Forward to

Destination " 08877665544 @

0123456789 must match exactly

New destination tel. number.

Example: CF to 08877665544 for 0123456789 telephone number of the account.

Pattern

Destination " 0123456789 @

Source " 007.* @

Presentation

Forward to

Destination " 08877665544 @

1. 0123456789 must match exactly.
2. The caller must come from Russia "007"

New destination tel. number.

Example: CF to the VoiceMail Box of telephone number 0123456789.

Pattern

Destination " 0123456789 @

Source " " @

Presentation

Forward to

Destination " *86 @

0123456789 must match exactly

Service 86 "VoiceMail Box"

Example: Reject anonymous calls toward telephone number 0123456789 of the account.

Pattern

Destination " 0123456789 @

Source " " @

Presentation Hide

Forward to

Destination " mcr_star99 @mediacenter

1. 0123456789 must match exactly.
2. Incoming call must be anonymous.

Standard in-band text "No Anonymous" at MediaCenter

Example: CF to "Test Announcement" with text ID "1" of telephone number 0123456789.

Pattern

Destination " 0123456789 @ "

Source " @ "

Presentation ▾

Forward to

Destination " mcf_message1 @ mediacenter "

0123456789 must match exactly.

Standard in-band text at the MediaCenter

The number after "*88", e.g., 1, is used for the new destination "mcf_message1".

*881

Announcement

Settings Interactions

Name Test Announcement

Announcementtext ▶ Play / Modify... Modify using phone

Immediately ▾

Music on wait ▾

Periodically ▾

Dest. not reachable ▾

After 10 Sec Restart ▾





10 Manage the Attributes of an Account


10.1 Overview Account Attributes

The account Attributes allow special configurations of e.g. limits, features that must be valid for just the account.

10.2 Configure the Account Attribute Parameters

Manage the account Attribute of an account in the ConfigCenter as Administrator/Operator:

- > Menu: Accounts
 - > The dialog "Accounts" is displayed.
 - > Click the row of the desired Account.
 - > Click the icon  at **Attributes** **1 Attribute** 
 - > The dialog "Attributes for Account: ..." is displayed. It allows:
 - ▶ To create a new Attribute, click icon 
 - ▶ Modify and delete an Attribute, click the row of the desired Attribute.
 - ▶ Delete an Attribute click icon  or click the button "Delete" in the dialog "Attribute: ..."



| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|---|-------------------------------------|
| Name | Selection | | Defines the Account Attribute name. |
| Value | String | [empty Value, max. 256 char] Default: empty | Defines the value of the attribute. |

10.3 List of the Account Attributes

| Account Attribute | Description |
|------------------------|--|
| maxPublicCalls | Defines the limit of connections of this Account via a gateway to and from the PSTN for this account. |
| maxPublicCallsIncoming | Defines the limit of connections of this Account via a gateway to and from the PSTN for this account. |
| maxPublicCallsOutgoing | Defines the limit of incoming connections of this Account via a gateway from the PSTN for this account. |
| teamsDomain | Defines for the feature "MS Teams Zero Touch" the customer's domain name and port where the Account expects to send and receive SIP messages with a zero-touch SBC. Example: c1.tms-provider.com:5070 |
| announcementProfile | Defines an audio file to be played to the caller before the call is routed and connected |
| worktimeFraud | Assigns for the Account a different Fraud Detection time slot duration than the defined value on anSwitch V6 system level. |
| nighttimeFraud | The value can be different for calls during working and non-working times and for international calls. |
| internationalFraud | |

11 Manage the Emergency Address

11.1 Overview of the Emergency Address

The Emergency Address data is additional information that is transferred to an emergency call center. Based on this data, the emergency services can perform more efficiently.

The concept of emergency locating according to the EU regulation NG112 is implemented according to the Swiss regulation (adaptations for other countries are possible).

- ▶ It requires that location information is collected and transferred to a centralized Location-Information-Service, LIS-server.
- ▶ The LIS-server returns a URL that needs to be passed as SIP-header to the emergency call.


11.2 Configure the Emergency Address Parameters


Manage the Emergency Address of an account in the ConfigCenter as Administrator/Operator:

For accounts:

- > Menu: Accounts
 - > The dialog "Accounts" is displayed.
 - > Click the row of the desired Account.

For addresses:

- > Menu: Addresses
 - > The dialog "Address" is displayed.
 - > Click the row of the desired Address.
- > Click the icon  at **Emergency Address** unknown
- > The dialog "Emergency Address for Account/Address: ..." is displayed.



| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|-----------------------------|--|
| Name | String | Max. 60 char | Defines the name of the addressee. |
| Street | String | Max. 60 char | Defines the street name of the city. |
| House Number | String | Max. 20 char | Defines the house number in the street. Swiss specific: Contrary to the standard, numbers and text are possible, so that e.g. 12a can be transmitted. |
| Building | String | Max. 60 char | Defines any information for identifying the building. The building information can occur in addition of the street name and hose number. |
| Postal Code | String | Max. 20 char | Defines the postal code of the city or street. |
| City | String | Max. 60 char | Defines the name of the city. |
| Country | String | Max. 60 char Default: CH | Defines the country 2-letter ISO code, for example: CH. |

| Parameter Name | Data Type | Allowed Values | Description |
|-----------------|-----------|--|---|
| | | | If the value is not provided during the configuration, then the default value CH is used. |
| Additional Code | String | Max. 50 char | Defines an additional information that can or must be provided. Swiss specific: The use of the Federal Building Identifier EGID:1234567 or VoIP Location Identifier VLI:12345678. |
| Circle Pos. | String | Max. 60 char | Defines the geographic location position, for example: 46.9469359 7.4352436 |
| Circle Radius | Float | Max. 60 char | Defines the measure of the uncertainty in determining the location position. The measure is in meter, for example: 30.0 |
| Method | Selection | [DHCP 802.11 CELL GNSS Manual] | Swiss specific: The following values are used for the delivery of VSP and ECSP in Switzerland: Value: <ul style="list-style-type: none"> ▶ DHCP IP localization from WireLine and private networks. ▶ 802.11 IP localization from Wifi Calling. ▶ CELL Cell localizations incl. TA/RTT for WireLess and Wifi Calling (LastCell). ▶ GNSS Satellite-based localization (GPS, A-GPS, etc.). ▶ Manual Are manually provisioned addresses and replace "Nomadic use" |

12 Manage Zone-Profiles for SIP-Device Configuration File Download

12.1 Overview Zone-Profiles



Zone-Profiles allow to define the SIP-phone configuration information. This Zone information is delivered to a SIP-phone when it requests its configuration file from the AdminCenter.


A Zone-Profile can be allocated in the SIP-Endpoint:

Menu: System > Sub-menu: SIP Endpoints > Dialog: SIP Endpoint: ...



12.2 Configuring Zone-Profile Parameters




Log in to the ConfigCenter as Administrator or Operator:

- > Menu: System
- > Sub-menu: Zone Profiles
- > The dialog "Web Profiles" is displayed. It allows:
 - ▶ To create a Zone-Profile, click icon 
 - ▶ Modify and delete a Zone-Profile, click the row of the desired profile.
 - ▶ Delete a Zone-Profile click icon  or click the button "Delete" in the dialog "Zone Profile: ..."



| Parameter Name | Data Type | Allowed Values | Description |
|-----------------|-----------|---|---|
| Name | String | [empty Name, max. 128 char] Default: empty | Defines the name of the Zone-Profile. |
| Key | String | [empty Key, max. 32 char] Default: empty | Defines the key for the Zone-Profile. |
| Extends profile | Selection | [- (none) List of configured Zone-Profile] Default: - (none) | Defines a parent profile and allows to extend or overwrite a parameter value of this profile. |

| Parameter Name | Data Type | Allowed Values | Description |
|--|--|--|---|
| | | | <p>Example:</p>  <p>Values:</p> <ul style="list-style-type: none"> ▶ - (none): No extension ▶ Zone-Profile: Defines the name of a parent Zone-Profile. |
| Parameters for the Configuration Access of the SIP Equipment: Basically, these parameters define where the SIP equipment, e.g. SIP-phone, must request its configuration file from the anSwitch V6. Due to the different configuration requirements of the various SIP device types, the same information must be configured several times. | | | |
| configProtocol | <input type="checkbox"/> String | Activate Default: Not activated [empty Value, max. 128 char] Default:  | Defines IP protocol to use when the parameters configIp, configPort or configUrl must be used in the generated configuration file. Valid values: <ul style="list-style-type: none"> ▶ http: Use the HTTP protocol. ▶ https: Use the HTTPS protocol |
| configIP | | | Defines the IP address where to download the configuration file. Valid values: <ul style="list-style-type: none"> ▶ x.x.x.x: IP address ▶ String: Domain name |
| configPort | | | Defines the IP port where to download the configuration file. Values: <ul style="list-style-type: none"> ▶ Number: IP port number |
| configUrl | | | Defines the full URL where to download the configuration file. Valid value: <ul style="list-style-type: none"> ▶ URL: URL, composed with the values of the parameters configProtocol, configIp and configPort. |
| configIpHttp | | | The same configuration options as for the configIp, configPort or configUrl parameters, but the protocol is fixed to HTTP. |
| configPortHttp | | | |
| configUrlHttp | | | |

| Parameter Name | Data Type | Allowed Values | Description |
|--|--|--|--|
| Parameters for Registering and Call Setup for the SIP Equipment at the anSwitch V6: | | | |
| sipAddress sipPort sipTransport | <input type="checkbox"/> String | Activate Default: Not activated [empty Value, max. 128 char] Default:  | Configure the IP address, IP port and protocol that is used in the SIP-Endpoint where this Zone-Profile is associated with. Example: SIP-Endpoint configuration:  Corresponding Zone-Profile configuration:  |
| sipIp | <input type="checkbox"/> String | Activate Default: Not activated [empty Value, max. 128 char] Default: empty | Defines a specific IP address configuration for the Patton SmartNode. The value is usually equal to the sipAddress parameter. |

13 Manage SIP-Profiles of Whitelisted IP-Networks for Phone Registration

13.1 Overview SIP-Profiles



SIP-Profiles allow to define from which IP-subnets a SIP-device, e.g. phone, is allowed to register to an Account.


A SIP-Profile can be allocated in the customer Account:

Menu: Accounts > ... > Dialog: Account: ... > Tab: Advanced

13.2 Configuring SIP Profile Parameters

Log in to the ConfigCenter as Administrator or Operator:

- > Menu: System
- > Sub-menu: SIP Profiles
- > The dialog "SIP Profiles" is displayed. It allows:
 - ▶ To create a SIP-Profile, click icon 
 - ▶ Modify and delete a SIP-Profile, click the row of the desired profile.
 - ▶ Delete a SIP-Profile click icon  or click the button "Delete" in the dialog "SIP Profile: ..."



| Parameter Name | Data Type | Allowed Values | Description | | | | | | | | | |
|-----------------|-------------------------------------|--|---|-----------|--------------------------|---------------|-----------|--------------------------|---------------|-----------|-------------------------------------|---------------|
| Name | String | [empty Name, max. 128 char] Default: empty | Defines the name of the SIP-Profile. | | | | | | | | | |
| Key | String | [empty Key, max. 32 char] Default: empty | Defines the key of the SIP-Profile. | | | | | | | | | |
| Extends profile | Selection | [- (none) List of configured SIP-Pro- files] Default: - (none) | Defines a parent profile and allows to extend or overwrite a network value. Example: <div><div>Extends profile workspace1-2</div><div>Restrict access to the following networks</div><table><tr><td>Network 1</td><td><input type="checkbox"/></td><td>10.10.10.0/24</td></tr><tr><td>Network 2</td><td><input type="checkbox"/></td><td>10.10.20.0/24</td></tr><tr><td>Network 3</td><td><input checked="" type="checkbox"/></td><td>10.10.30.0/24</td></tr></table></div> Values: <ul style="list-style-type: none">▶ - (none): No extension▶ SIP-Profile: Defines the name of a parent SIP-Profile. | Network 1 | <input type="checkbox"/> | 10.10.10.0/24 | Network 2 | <input type="checkbox"/> | 10.10.20.0/24 | Network 3 | <input checked="" type="checkbox"/> | 10.10.30.0/24 |
| Network 1 | <input type="checkbox"/> | 10.10.10.0/24 | | | | | | | | | | |
| Network 2 | <input type="checkbox"/> | 10.10.20.0/24 | | | | | | | | | | |
| Network 3 | <input checked="" type="checkbox"/> | 10.10.30.0/24 | | | | | | | | | | |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|--|--|
| Network 1 | String | Activate Default: Not activated [empty IP network address, in x.x.x.x/yy notation] Default: empty | If activated, defines the allowed IP-network. Example: <div> <div>Network 1 <input checked="" type="checkbox"/> 10.10.10.0/24</div> <div>Network 2 <input checked="" type="checkbox"/> 10.10.20.0/24</div> <div>Network 3 <input type="checkbox"/> x.x.x.x/yy</div> </div> |
| Network 2 | | | |
| Network 3 | | | |

14 Manage Web-Profiles of Whitelisted IP-Networks for AdminCenter Access

14.1 Overview Web-Profiles



Web-Profiles allow to define from which IP-subnets a user's Web browser is allowed to access the AdminCenter user interface.



A Web-Profile can be allocated in the Address:

Menu: Address > ... > Dialog: Address: ... > Tab: Advanced > Link: AdminCenter Access

14.2 Configuring Web-Profile Parameters

Log in to the ConfigCenter as Administrator or Operator:

- > Menu: System
- > Sub-menu: Web Profiles
 - > The dialog "Web Profiles" is displayed. It allows:
 - ▶ To create a Web-Profile, click icon 
 - ▶ Modify and delete a Web-Profile, click the row of the desired profile.
 - ▶ Delete a Web-Profile click icon  or click the button "Delete" in the dialog "Web Profile: ..."

| Parameter Name | Data Type | Allowed Values | Description |
|-----------------|--|--|---|
| Name | String | [empty Name, max. 128 char] Default: empty | Defines the name of the Web-Profile. |
| Key | String | [empty Key, max. 32 char] Default: empty | Defines the key for the Web-Profile. |
| Extends profile | Selection | [- (none) List of configured Web-Pro- files] Default: - (none) | Defines a parent profile and allows to extend or overwrite a network value. Example:  Values: ▶ - (none): No extension ▶ Web-Profile: Defines the name of a parent Web-Profile. |
| Network 1 | <input type="checkbox"/> String | Activate Default: Not activated | If activated, defines the IP-network. Example  |
| Network 2 | | [empty IP network address, in x.x.x.x/yy notation] Default: empty | |
| Network 3 | | | |

15 Manage SIP-Trunk Profiles for SIP Equipment Communication

15.1 Overview of the SIP-Trunk Profile

A customer Account needs a SIP-Trunk when the customer's SIP equipment does not or cannot use the standard SIP Registration process.

When no SIP Registration is possible then the anSwitch V6 has to learn "manually":

- ▶ IP address → Where is the peering SIP equipment located in the IP network.
- ▶ Authentication → How can the anSwitch V6 make sure that a SIP message is coming from the correct peering SIP equipment.
- ▶ Caller Identification → Which delivered caller number must be used for the caller-ID verification by the anSwitch V6.

→ This information is configured in the SIP-Trunk Profiles.


A SIP-Trunk Profile can be allocated in the customer Account:

Menu: Accounts > ... > Dialog: Account: ... > Tab: Basic > Link: SIP Trunks

15.2 Use Cases of SIP-Trunk Profiles


Use Case: Non-registering SIP equipment with own public IP.

The customer's SIP equipment has a direct public IP-address.




Use Case: Non-registering SIP equipment behind Session Border Controller SBC.

The customer's SIP equipment is hidden by a Session Border Controller SBC.



Use Case: Non-registering SIP equipment behind NAT.

The customer's SIP equipment has a private IP-address and is hidden by a NAT'ing IT equipment, e.g. access router, firewall.




Use Case: Redundant SIP-Trunk setup with weighted outgoing SIP message transmission.

The customer requests a redundant SIP-Trunk interconnection between the anSwitch V6 and the own SIP equipment:

- ▶ >1 SIP-Trunk profiles can be associated with the customer Account.
- ▶ Each SIP-Trunk profile can be designed to suit the peering needs.

- ▶ The SIP-Trunk profile can be weighted for managing the outgoing workload toward the peering equipment.




Use Case: Shared SIP-Trunk

The customer requests a shared SIP-Trunk interconnection between the anSwitch V6 and the own SIP equipment.



For example, due to:


- ▶ The customer's user groups shall have different pricelists.
- ▶ Separate CDR-CSV files are created on the anSwitch V6 for the customer's user groups billing.



15.3 Configuring the SIP-Trunk Profile Parameters

Log in to the ConfigCenter as Administrator or Operator:

- > Menu: System
- > Sub-menu: SIP Trunks
- > The dialog "SIP Trunks" is displayed. It allows:
 - ▶ To create a SIP-Trunk, click icon 
 - ▶ Modify and delete a SIP-Trunk, click the row of the desired profile.
 - ▶ Delete a SIP-Trunk click icon  or click the button "Delete" in the dialog "SIP Trunk: ..."



| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|--|---|
| Group | Selection | [- (none) List of configured Group] | Defines that the SIP-Trunk profile belongs to a specific Group. |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|----------------|--|--|
| | | Default: - (none) | Values: <ul style="list-style-type: none"> ▶ - (none): No Group assigned. ▶ Group: Defines a Group whose members can select this SIP-Trunk Profile. Note: With this selection this SIP-Trunk profile is visible only for the accounts of this group. |
| Accounts | Display & link | Accounts 1 Account ➡ | Displays the number of accounts using this SIP-Trunk profile. ➡ is the link to the list of accounts using this SIP-trunk profile. |
| Name | String | [empty Name, max. 32 char] Default: empty | Defines the name of the SIP-Trunk profile. |
| Info | String | [empty Max. 128 char] Default: empty | Any information about this SIP-Trunk profile. |

Parameters for the Authentication of the Peering SIP Equipment:

▶ **Authentication variant 1:**
The customer SIP-equipment can answer a **challenge** of the anSwitch V6 with correct SIP-credentials.


a. Configure the authentication parameters for checking with challenging:

- ▶ "Authentication" Select "Challenge"

b. The customer must configure the SIP authentication with SIP-credentials in the customer SIP-equipment.

Configuration SIP-Equipment:
Authentication:
▶ SIP-Credential
▶ Main Number

1. Variant: Challenge & Check SIP-Credentials




Authentication variant 2:
The anSwitch V6 checks against the **source IP address** (and optional IP port) of the received IP-packets containing SIP-messages.

a. Configure the authentication parameters for checking just the IP-packet source:

- ▶ SIP-equipment behind IT-device with **NAT**
 - ▶ "Authentication" Select "Source IP", as the IP port may change.
- ▶ SIP-equipment behind **firewall** with exposed public IP address and port
 - ▶ "Authentication" Select "Source IP" or "Source IP and Port"

b. The customer must configure the SIP-equipment and IT-devices so that they match the authentication requirements of the anSwitch V6.

2. Variant: Check Source IP & Port



SIP Trunk: Trk-A

Group: Provider A

Accounts: 1 Account

Name: Trk-A

Info: SIP-Trunk for Account: Acc-A

Authentication: Challenge

CPE-Contact: sip:11.11.11.11:5560

Route 1:

Route 2:

User-Agent:

SIP Endpoint: Public, 5060



Weight: 1000

Find Address: Using preferred number



On no match: Reject call

NAT Config: No NAT


Ok Save Delete Close



| Parameter Name | Data Type | Allowed Values | Description |
|--|-----------|--|--|
| <p>► Authentication variant 3:</p> <p>The anSwitch V6 checks against the source IP address and IP port of the last SIP-header VIA of the received SIP-message.</p> <p>a. Configure the authentication parameters for checking the SIP-equipment behind an IT-device with NAT and the contact port from within the SIP-message.</p> <p>► SIP-equipment behind IT-device with NAT</p> <p>► "Authentication"</p> <p>Select "Source IP and Contact-Port"</p> <p>► "CPE-Contact"</p> <p>Configure the CPE-contact IP address or domain name and the used IP-port for SIP of the SIP-equipment, e.g., 6660</p> <p>b. The customer must configure SIP authentication in the SIP-equipment.</p> | |  <p>3. Variant:</p> <p>Check Source IP = CPE-Contact</p> <p>Check remote port of last SIP-Header VIA: 192.168.0.100:6660;received=11.11.11.11:...</p> | |
| <p>► Authentication variant 4:</p> <p>The anSwitch V6 checks against the source IP address and compares the remote IP information of the last SIP-header VIA with the value of Route 1.</p> <p>a. Configure the authentication parameters for checking the SIP-equipment behind an SBC.</p> <p>► "Authentication"</p> <p>Select "Source and Remote-Address" then the complete remote IP and port are matched against the "Route 1" value.</p> <p>Select "Source and Remote-IP" then the remote IP address is matched against the IP address value of "Route 1".</p> <p>b. The customer must configure the SIP-equipment and IT-devices so that they match the authentication requirements of the anSwitch V6</p> | |  <p>4. Variant:</p> <p>Check Source IP = CPE-Contact</p> <p>Check the address of the last SIP-Header VIA: 33.33.33.33:5062;received=33.33.33.33:...</p> | |
| Authentication | Selection | <p>[Challenge Source IP Source IP and Port Source IP and Contact-Port Source and Remote-Address Source and Remote-IP]</p> <p>Default: Challenge</p> | <p>Defines how the peer SIP equipment has to authenticate in order that outgoing calls by the peering SIP equipment are processed.</p> <p>Values:</p> <p>► Challenge:</p> <p>The peering SIP equipment is challenged by the anSwitch V6 call control. The peering SIP equipment must authenticate with the SIP username and password defined in the associated SIP.</p> <p>► Source IP:</p> <p>► Source IP and Port:</p> <p>The anSwitch V6 call control checks the IP address/port of the received IP packet against the IP address/port defined in parameter "CPE-Contact".</p> <p>► Source IP and Contact-Port:</p> <p>The anSwitch V6 call control checks the IP address against the IP address defined in parameter "CPE-Contact" and additionally the contact IP port within the SIP-message against the IP port defined in parameter "CPE-Contact".</p> |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-------------|--|--|
| | | | <ul style="list-style-type: none"> ▶ Source and Remote-Address: ▶ Source and Remote-IP: The anSwitch V6 call control checks of the received IP packet either the complete-address data or just the IP-address against the address data defined in parameter "Route 1"CPE-Contact". |
| Route 1 | SIP-Address | [empty SIP-Address, max. 128 char] Default: empty | <p>If an intermediate SIP-manipulating device, e.g. a Session Border Controller SBC, is used, "Route 1" defines the IP address or the domain name and the port of this SIP-manipulating device, which points to the anSwitch V6.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: No intermediate SIP-manipulating device. ▶ SIP-Address: Defines the IP address. For example: sip:33.33.33.33:5062 sip:sbc.customer-company.com:5062 |
| Route 2 | SIP-Address | [empty SIP-Address, max. 128 char] Default: empty | <p>If an intermediate SIP-manipulating device, e.g. a Session Border Controller SBC, is used, "Route 2" defines the IP address or the domain name and the port of this SIP-manipulating device, which points to the customer's peering SIP equipment.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: No intermediate SIP-manipulating device. ▶ SIP-Address: Defines the IP address. For example: sip:22.22.22.22:5065 sip:sbc.customer-company.com:5065 |

| Parameter Name | Data Type | Allowed Values | Description |
|--|-------------|--|---|
| Parameters for Processing Incoming and Outgoing SIP-Message: | | | |
| <div> <div> <p>Configuration Scenario 1:</p> <ul style="list-style-type: none"> SIP-equipment is behind a firewall with exposed fix public IP and port. SIP-equipment is behind IT-device with NAT <ul style="list-style-type: none"> → The public IP address is assigned by the ISP. → This IP address must remain fix! <p>a. Configure the SIP-Trunk profile parameter:</p> <ul style="list-style-type: none"> "CPE-Contact" <ul style="list-style-type: none"> Configure the IP address or domain name and port where the anSwitch V6 must send its SIP-messages, e.g.: sip:11.11.11.11:5560 sip:sip.customer-company.com:5560 "SIP Endpoint" <ul style="list-style-type: none"> Select the SIP Endpoint where the SIP-messages from the peering customer SIP-equipment are received. → The IP address and port of this SIP Endpoint must be configured in the customer SIP-equipment. "NAT Config" <ul style="list-style-type: none"> Select according the situation of the customer SIP-equipment. ▶ "Behind NAT" ▶ "No NAT" ▶ "Automatic": only if the situation is unknown. </div> <div>  <p>Configuration Scenario 2:</p> <ul style="list-style-type: none"> SIP-equipment is behind a Session Border Controller SBC. <p>a. Configure the SIP-Trunk profile parameter:</p> <ul style="list-style-type: none"> "CPE-Contact" <ul style="list-style-type: none"> Configure the IP address or domain name and port where the anSwitch V6 must send its SIP-messages, e.g.: sip:33.33.33.33:5560 sip:sbc.customer-company.com:5560 "Route 1" → Toward anSwitch V6 "Route 2" → Toward customer SIP-equipment Configure the IP-address according the SBC settings. "SIP Endpoint" <ul style="list-style-type: none"> Select the SIP Endpoint where the SIP-messages from the peering customer SIP-equipment are received. → The IP address and port of the SIP Endpoint must be configured in the SBC. "NAT Config" <ul style="list-style-type: none"> Select "No NAT" </div> <div>  </div> </div> | | | |
| CPE-Contact | SIP-Address | [empty SIP-Address, max. 128 char] Default: empty | <p>Defines the IP address or domain name and port where the anSwitch V6 must send its SIP-messages toward the peering SIP equipment.</p> <p>Depending on the IP environment of the customer side the CPE-Contact may be:</p> <ul style="list-style-type: none"> ▶ A fixed public IP address of the: <ul style="list-style-type: none"> ▶ SIP equipment. ▶ Firewall or Session Border Controller SBC proxying the SIP-messages to the SIP equipment. ▶ Volatile public IP address of a NATing IP device, e.g. access router. <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: No SIP-messages can be sent. ▶ SIP-Address: Defines the IP address. For example: sip:33.33.33.33:5560 sip:sbc.customer-company.com:5560 |
| SIP Endpoint | Selection | [- (none) List of configured SIP-Endpoints] | Defines the SIP Endpoint where the SIP-messages from the peering customer SIP equipment are received. |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|--|---|
| | | Default: - (none) | <p>Values:</p> <ul style="list-style-type: none"> ▶ - (none): No incoming SIP-messages are processed by the anSwitch V6 call control. ▶ SIP-Endpoint: Defines the SIP-Endpoint where the anSwitch V6 accepts incoming SIP-messages from the peering SIP equipment. <p>Note: The IP address and port of this SIP-Endpoint must be configured in the customer SIP equipment.</p> |
| NAT Config | Selection | <p>[Automatic Behind NAT No NAT]</p> <p>Default: Automatic</p> | <p>Defines if the peering SIP equipment is located behind a NATing IT-device, e.g. a customer's access router.</p> <p>If a NATing IT-device is involved, then it must be made sure that the NAT port for the SIP-messages remains open all the time. If the NAT port closes unexpectedly, then no incoming calls to the peering SIP equipment can be signaled by the anSwitch V6.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ Automatic: The anSwitch V6 tries to find out if the peering SIP equipment is behind a NATing IT-device. If yes, then the anSwitch V6 makes sure that the NAT port remains open. ▶ Behind NAT: Defines that the peering SIP equipment is behind a NATing IT-device. The anSwitch V6 makes sure that the NAT port remains open. ▶ No NAT: Defines that the peering SIP equipment is not behind a NATing IT-device. <p>Note: Select "Automatic" only if the situation is unknown.</p> |
| User-Agent | String | <p>[empty Name, max. 256 char]</p> <p>Default: empty</p> | <p>Defines the application a specifically developed anSwitch V6 Capability-Set that solves interoperability problems between the customer SIP equipment and the anSwitch V6.</p> <p>Values:</p> <ul style="list-style-type: none"> ▶ empty: Standard SIP and audio stream processing is applied. ▶ Name: Defines the anSwitch V6 Capability-Set to be used. |

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|--|--|
| | | | Note: For developing, creating and activating a Capability-Set an Aarenet system engineer is required. Contact your Aarenet account manager for an interoperability project! |
| Weight | Number | 0 - 1000 Default: 1000 | <p>The SIP-Trunk profile can be weighted for managing the outgoing SIP-message workload toward the peering SIP equipment.</p> <p>Examples:</p> <ul style="list-style-type: none"> ▶ Trk-A = 500, Trk-B = 500 : The anSwitch V6 load balances outgoing calls 50% on Trk-A and 50% on Trk-B ▶ Trk-A = 1000, Trk-B = 0 : All outgoing calls are routed via Trk-A. If the connectivity via A fails all outgoing calls are routed via Trk-B. <p>Values:</p> <ul style="list-style-type: none"> ▶ 0 - 1000: Balanced outgoing SIP-message load via this SIP-Trunk. <p>Note: Incoming calls are accepted in any case from both SIP-trunks.</p> |
| | |  | <div style="border: 1px solid black; padding: 5px;"> <p>SIP-Trunk: "Trk-A" CPE-Contact: 11.11.11.11:5560 Weight: 500</p> </div> <div style="border: 1px solid black; padding: 5px;"> <p>SIP-Trunk: "Trk-B" CPE-Contact: 12.12.12.12:5560 Weight: 500</p> </div> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Account: "Acc-A"</p> <p>SIP-Credentials Main Number: 0222222000 Numbers: 0222222001-99 SIP Trunk: Trk-A Trk-B</p> </div> |

| Parameter Name | Data Type | Allowed Values | Description | | | | | | | | | | | | | | | |
|---|--|---|--|---|----------------------|------------------------------|----------------|--|--|---|---|---|--|---|--|---|--|--|
| Parameters for Handling the Caller-ID Verification <ul style="list-style-type: none">As Class 5 switch the anSwitch V6 is required on an outgoing call to verify the Caller-Id and set the correct caller information.We probably don't know what caller information and combinations are sent by the customer SIP equipment. | | | | | | | | | | | | | | | | | | |
| <div></div> | | | | | | | | | | | | | | | | | | |
| Find Address | Selection | [Using preferred number Using asserted number] Default: Using preferred number | Defines which SIP-header must be used by the anSwitch V6 call control for the caller-ID evaluation. Values: <ul style="list-style-type: none">Using preferred number: Defines the number of the SIP Header P-Preferred must be used.Using asserted number: Defines the number of the SIP Header P-Asserted must be used. | | | | | | | | | | | | | | | |
| <div></div> <table><thead><tr><th>Possible INVITE SIP-Header Combinations</th><th>anSwitch V6 Behavior</th><th>"Find Address" Configuration</th></tr></thead><tbody><tr><td>From: 08001234</td><td>The "Find Address" setting is ignored.</td><td>The "Find Address" setting is ignored.</td></tr><tr><td>From: 0222222001 P-Preferred: 08001234</td><td>The P-Preferred or P-Asserted is used according the configuration for the "Find Address".</td><td>Select "Using preferred number" or "Using asserted number" according which SIP-header contains the desired caller number.</td></tr><tr><td>From: 08001234 P-Asserted: 0222222001</td><td>The FROM is used as fall back for a missing P-Preferred or P-Asserted in the INVITE</td><td></td></tr><tr><td>From: 08001234 P-Preferred: 08001234 P-Asserted: 0222222001</td><td>The P-Preferred or P-Asserted are used according the configuration for the "Find Address". The FROM is ignored.</td><td>Best Practice: Use "Using asserted number " if P-Asserted is available.</td></tr></tbody></table> | | | | Possible INVITE SIP-Header Combinations | anSwitch V6 Behavior | "Find Address" Configuration | From: 08001234 | The "Find Address" setting is ignored. | The "Find Address" setting is ignored. | From: 0222222001 P-Preferred: 08001234 | The P-Preferred or P-Asserted is used according the configuration for the "Find Address". | Select "Using preferred number" or "Using asserted number" according which SIP-header contains the desired caller number. | From: 08001234 P-Asserted: 0222222001 | The FROM is used as fall back for a missing P-Preferred or P-Asserted in the INVITE | | From: 08001234 P-Preferred: 08001234 P-Asserted: 0222222001 | The P-Preferred or P-Asserted are used according the configuration for the "Find Address". The FROM is ignored. | Best Practice: Use "Using asserted number " if P-Asserted is available. |
| Possible INVITE SIP-Header Combinations | anSwitch V6 Behavior | "Find Address" Configuration | | | | | | | | | | | | | | | | |
| From: 08001234 | The "Find Address" setting is ignored. | The "Find Address" setting is ignored. | | | | | | | | | | | | | | | | |
| From: 0222222001 P-Preferred: 08001234 | The P-Preferred or P-Asserted is used according the configuration for the "Find Address". | Select "Using preferred number" or "Using asserted number" according which SIP-header contains the desired caller number. | | | | | | | | | | | | | | | | |
| From: 08001234 P-Asserted: 0222222001 | The FROM is used as fall back for a missing P-Preferred or P-Asserted in the INVITE | | | | | | | | | | | | | | | | | |
| From: 08001234 P-Preferred: 08001234 P-Asserted: 0222222001 | The P-Preferred or P-Asserted are used according the configuration for the "Find Address". The FROM is ignored. | Best Practice: Use "Using asserted number " if P-Asserted is available. | | | | | | | | | | | | | | | | |
| On no Match | Selection | [Reject call Continue authentication] Default: Reject call | Defines what has to be done when no valid caller-ID can be identified by the anSwitch V6. Values: <ul style="list-style-type: none">Reject call: The call shall be rejected (SIP cause 401).Continue authentication: The anSwitch V6 challenges for the SIP-credentials and will route the call if successful. | | | | | | | | | | | | | | | |


16 Manage Default Configuration Values of a Customer Account

16.1 Overview to the Default Configuration Values

For the configuration of customer accounts via the ConfigurationCenter, it is possible to define default values for the organization unit types system and tenant.

When default configuration values are configured, e.g. for a certain tenant, then they will be applied when a new customer account is created of the organization unit.

For example: The default configuration values for Tenant "Provider A"



The following values apply for this tenant
Tenant: Provider A

Accounts | Addresses | AdminCenter

Default values for new accounts of tenant Provider A

Account Name: ACC_Test-????
Username: ??????????
Password: ??????????
Routing Table: RT_to_PSTN All
Pricelist: PL Customer USD
Ruleset: Route: Subscriber
Advice of Charge: None
Special Arrangement: No
Alarm on Expiry: No
TopStop Alarm: 50%
Alarm E-mail: noc@provider-a.com
TopStop Maximum Value: 20.00
Daily TopStop: No
Daily Maximum Charge: 0.00

Accounts | **Addresses** | AdminCenter

Default values for new Addresses of tenant Provider A

Domain: sip.provider-a.com
Address Present:
Language: English
Multiple registrations: Weighted
Default values for new Answering Machines of tenant Provider A
Self create Answering Machine:
Password:
Access without Password:
Signaling: Only explicit MWI subscriptions

Accounts | Addresses | **AdminCenter**

Default values for new accounts of tenant Provider A

Create Access for new accounts:
Username for new account access:
Password for new account access:
Language for new account access: English
Default values for new Addresses of tenant Provider A
Create access for new addresses:
Password for new address access:
Language for new address access: English

16.2 Configuring the Default Configuration Parameters


Manage the default configuration values as Administrator/Operator:

- > Menu: System
- > Sub-menu: Default Values

| Parameter Name | Data Type | Allowed Values | Description |
|----------------|-----------|---|---|
| Tenant | Selection | [empty List of configured Tenants] Default: empty | Defines the organization unit the default values are associated with. Values: <ul style="list-style-type: none"> ▶ empty: The defined default values are applied to the organization unit "System". ▶ Tenant: The defined default values are applied to the organization unit "Tenant". |

The configuration of the available default parameters is identical to their description:

Configuring the Account Parameter 

Configuring the Address Parameter 

17 Deprecated Account and Address Features

The following Account and Address features and their configuration menus in the ConfigCenter are deprecated.

Note

Their configuration is still possible, but their functionality is no longer being further developed and errors are not being corrected.


- ▶ The feature vPBX is deprecated and all its specific configuration.
 - ▶ Address configuration
Menu: Address > Dialog: Address: ... > Tab: virtual PBX
 - ▶ PBX Wizard
Menu: System > Sub-Menu: PBX Wizard
 - ▶ Call distributions
Menu: Accounts > Dialog: Account: ... > Sub-Menu: Call Forwards
- ▶ Veeting UCC interconnection configuration
Menu: System > Sub-Menu: System Settings
- ▶ WebRTC application interconnection configuration
Menu: System > Sub-Menu: RTC Accounts

18 Best Practices

18.1 Limit Temporarily an Account

Situations may arise in which the use of an account must be temporarily restricted, e.g. in the case of a non-paying customer. But due to possible legal obligations, a user must still be able to do emergency calls.


In such a situation it is not recommended to invalidate an account with "Valid until" or setting its channels to 0:



Best Practice

Temporarily limit an "Account" for outgoing calls but not calls to emergency numbers:

➔ Invoke the blocking ruleset "Block: All outgoing but emergency Calls"



18.2 Shutdown an Account

18.2.1 Different Shutdown Scenarios


Different "shutdown" scenarios for an Account are possible, when for example the customer terminates the telephony service contract.

For example:

- ▶ Delete an Account immediately.
All services and resources are immediately unavailable.
➔ All configurations of the Account and user data like VoiceMail Box messages, will be unrecoverable deleted. The CDR data are not deleted.
- ▶ Delete an Account after an administrative timeout:
The services and resources are in first step disabled for a certain time. After the administrative timeout, e.g. 6 month, the Account will be deleted.
This scenario may be suitable or needed due to:
 - ▶ Number porting to a new telephone provider.

- ▶ Blocking of the telephone numbers for a certain period of time before they are to be used again.
- ▶ You expect that the customer will come back soon.

Example flowchart for the "Shutdown" scenarios




Note

The desired shutdown process must be defined by the telephony provider.

18.2.2 Disabling an Account

As Operator disable an Account by configuring a "Valid until" date/time:

- ▶ No calls to and from this account are possible from this date/time on.
- ▶ No AdminCenter access is possible from this date/time on.



Account: aan1-demo-training

Channels 0 Channels

Addresses 1 Address

Call Forwards 0 Call Forwards

Attributes 0 Attributes

Basic Routing & Rating **Advanced**

Valid from 2018/08/01 00:00 until 2019/01/01 00:00

Special Arrangement No

Alarm on Expiry No

Use always Media Server No

Force Call ID (MCID) No

Music on Hold Transparent No

Network(s) SIP Profile


Ok Save Delete Close


Note

By invalidate an Account by "Valid until" the Operator can reactivate the Account easily when, e.g. an number porting process failed or a customer wants to come back.

18.2.3 Deleting an Account

As Operator disable an Account:


1. Search for the Account in the ConfigCenter.
2. Click the  and confirm the delete command.



| Account | Info | Tenant |
|---------------------------|----------------------------------|--------|
| aan1-training-residential | Training Account; Tel 0987654321 | aan1 |

or

3. Open the Account dialog.
4. Click button [Delete] and confirm the delete command.



Note

By deleting the Account, all associated phone numbers, messages in the VoiceMail Boxes, etc. will be deleted too!

19 Terms of Use

Intellectual Property Rights

All information including but not limited to documents, text, graphics and software available through the manual, are protected by copyright, trademark, and/or other intellectual property laws, and any unauthorized use of the information may violate such laws and this Agreement. Except as expressly provided herein or pursuant to a separate license agreement, Aarenet does not grant any express or implied rights to use the information. In addition, you agree not to use any data mining, robots, or similar data gathering methods relating to the website.

Links to Other Websites

The manual may contain links to third-party websites. Aarenet does not control such websites, nor do we accept any liability with respect to the content, accuracy or completeness of such websites. These third-party links are provided only as information.

Trademark Information

Provided previous written consent and approval has been delivered by Aarenet, you may refer to Aarenet's names, marks, brands, logos, designs and other designations provided that such reference is truthful and not misleading and complies with Aarenet's design rules and guidelines. Any such information may not be changed, manipulated, or used in any inconsistent way with Aarenet's ownership of such information. All use of such information shall be used only to the sole benefit of Aarenet or the promotion of Aarenet's products and services.

Limited Right to Use, Warranties and Disclaimer

Unless otherwise expressly agreed in writing by Aarenet, the viewing, printing or downloading of any material from the website grants you only a limited, nonexclusive license for use solely by you for personal, internal, non-commercial purposes and not for republication, distribution, assignment, sublicense, sale, preparation of derivative works or other use. No part of any materials may be reproduced in any form or incorporated into any information retrieval system, electronic or mechanical, other than for your personal, internal, non-commercial use (but not for resale or redistribution) unless otherwise expressly agreed in writing by Aarenet.

Last Page

| Date | Doc-ID | Description | Changes |
|-----------|----------------------------|-----------------------------------|---------|
| 28.5.2024 | manual_as6_2_operation_e08 | Document as preliminary published | |